




- NOTES:
1. MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
  2. STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE.
  3. KEY DIMENSIONS EQUAL (MOTOR SUPPLIED WITH KEY)
- 0.375" x 0.375" x 2.88"

UNITS: INCHES

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT WITHOUT NOTICE. DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS CERTIFIED.

## 250TC NEMA-BA TEFC FRAME F1 ASSEMBLY

MDSL049-04

# TOSHIBA

TOSHIBA INTERNATIONAL CORPORATION

### TOLERANCES

|       |       |
|-------|-------|
| .X    | .1    |
| .XX   | .03   |
| .XXX  | .005  |
| .XXXX | .0005 |

### MAXIMUM MOTOR WEIGHT

340 lbs.  
154 kgs.

| NO | REVISION                                 | DRAWN BY  | DATE     | CHECK |
|----|------------------------------------------|-----------|----------|-------|
| 1  | ADDED KEY DIMENSIONS (OVERRIDE 'R' DIM.) | S. CLANCY | 08/08/12 | JR    |
| 0  | FIRST ISSUE                              | N. MOMIN  | 11/09/10 | JR    |
| NO |                                          |           |          |       |

**EQP Global 840**  
**XT SERIES**

DRAWN BY: N. MOMIN  
CHECK BY: J. RUSSELL  
APPROVED BY: \_\_\_\_\_  
www.toshiba.com/ind

## TYPICAL MOTOR PERFORMANCE DATA

Model: 0106XSSC47A-P

| HP        | kW  | Pole       | FL RPM | Frame | Voltage        | Hz          | Phase    | FL Amps      |
|-----------|-----|------------|--------|-------|----------------|-------------|----------|--------------|
| 10        | 7.5 | 6          | 1170   | 256TC | 575            | 60          | 3        | 11           |
| Enclosure | IP  | Ins. Class | S.F.   | Duty  | NEMA Nom. Eff. | NEMA Design | kVA Code | Ambient (°C) |
| TEFC      | 55  | F          | 1.15   | CONT  | 91             | B           | G        | 40 C         |

| Load         | HP   | kW  | Amperes | Efficiency (%) | Power Factor (%) |
|--------------|------|-----|---------|----------------|------------------|
| Full Load    | 10   | 7.5 | 10.8    | 91.2           | 80.2             |
| ¾ Load       | 7.50 | 5.6 | 7.8     | 91.1           | 76.0             |
| ½ Load       | 5.00 | 3.7 | 6.1     | 89.5           | 66.3             |
| ¼ Load       | 2.50 | 1.9 | 4.8     | 82.6           | 46.4             |
| No Load      |      |     | 4.3     |                |                  |
| Locked Rotor |      |     | 62.00   |                |                  |

| Torque            |                      |                 |                    | Rotor wk² Inertia (lb-ft²) |
|-------------------|----------------------|-----------------|--------------------|----------------------------|
| Full Load (lb-ft) | Locked Rotor (% FLT) | Pull Up (% FLT) | Break Down (% FLT) |                            |
| 44.9              | 255                  | 250             | 285                | 2.65                       |

| Safe Stall Time(s) |     | Sound Pressure dB(A) @ 1M | Bearings* |          | Approx. Motor Weight (lbs) |
|--------------------|-----|---------------------------|-----------|----------|----------------------------|
| Cold               | Hot |                           | DE        | NDE      |                            |
| 35                 | 15  | -                         | 6309ZZC3  | 6309ZZC3 |                            |

\*Bearings are the only recommended spare part(s).

### Motor Options:

Mounting:C-Face Footed,Shaft:T Shaft

|             |  |
|-------------|--|
| Customer    |  |
| Customer PO |  |
| Sales Order |  |
| Project #   |  |

Tag:

All characteristics are average expected values.

**TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.**


|             |           |                  |             |             |               |
|-------------|-----------|------------------|-------------|-------------|---------------|
| Engineering | garce     | Doc. Written By  | D. Suarez   | Doc.# / Rev | MPCF-1119 / 0 |
| Engr. Date  | 8/21/2015 | Doc. Approved By | M. Campbell | Doc. Issued | 6/8/2011      |

## SPEED TORQUE/CURRENT CURVE

Model: 0106XSSC47A-P

| HP                | kW                                                  | Pole              | FL RPM           | Frame       | Voltage        | Hz             | Phase    | FL Amps      |
|-------------------|-----------------------------------------------------|-------------------|------------------|-------------|----------------|----------------|----------|--------------|
| 10                | 7.5                                                 | 6                 | 1170             | 256TC       | 575            | 60             | 3        | 11           |
| Enclosure         | IP                                                  | Ins. Class        | S.F.             | Duty        | NEMA Nom. Eff. | NEMA Design    | kVA Code | Ambient (°C) |
| TEFC              | 55                                                  | F                 | 1.15             | CONT        | 91             | B              | G        | 40 C         |
| Locked Rotor Amps | Rotor wk <sup>2</sup> Inertia (lb-ft <sup>2</sup> ) | Torque            |                  |             |                |                |          |              |
|                   |                                                     | Full Load (lb-ft) | Locked Rotor (%) | Pull Up (%) |                | Break Down (%) |          |              |
| 62.00             | 2.65                                                | 44.9              | 255              | 250         |                | 285            |          |              |

### Design Values



|             |  |                                                    |     |
|-------------|--|----------------------------------------------------|-----|
| Customer    |  | wk <sup>2</sup> Load Inertia (lb-ft <sup>2</sup> ) | -   |
| Customer PO |  | Load Type                                          | -   |
| Sales Order |  | Voltage (%)                                        | 100 |
| Project #   |  | Accel. Time                                        | -   |

Tag:



All characteristics are average expected values.

TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.

|             |           |                  |             |             |               |
|-------------|-----------|------------------|-------------|-------------|---------------|
| Engineering | garce     | Doc. Written By  | D. Suarez   | Doc.# / Rev | MPCF-1121 / 0 |
| Engr. Date  | 8/21/2015 | Doc. Approved By | M. Campbell | Doc. Issued | 6/8/2011      |

### Motor Connection Diagram

#### 3 Leads - Delta Connection



Switch L1 and L2 to reverse rotation

Each lead may consist of more than one cable.  
If multiple cables represent a single lead, each one  
of them will be labeled with the appropriate lead number.