

Straight Blade Devices
15 and 20 Ampere, 250 Volts
 2 Pole, 3 Wire Grounding
Insulgrip® Plugs and Flanged Inlets




Fed.Spec.




HBL5666C



HBL5666CA



HBL5666VY



HBL5678C

Plugs

Description	Cord Diameter	Catalog Number	
Insulgrip® Plug, black and white nylon.	.230"-.720" (5.8-18.3)	HBL5666C	HBL5466C
Insulgrip® Plug, corrosion resistant, yellow nylon.	.230"-.720" (5.8-18.3)	HBL56CM66C	HBL54CM66C
8-Position Insulgrip® Angle Plug, black and white nylon.	.325"-.655" (8.3-16.6)	HBL5666CA	HBL5466CA
Valise® Plug, yellow nylon.	.220"-.660" (5.6-16.8)	HBL5666VY	HBL5464VY

Note: See page A-47 for accessories.



15A 250V
 NEMA 6-15P
 UL CSA
 1.5 HP



20A 250V
 NEMA 6-20P
 UL CSA
 2 HP

Insulgrip® Flanged Inlets

Description	Catalog Number	
Nylon casing, back wired.	HBL5678C	HBL5478C

*Note: Flanged inlets are not HP rated.
 See page A-47 for accessories.*



15A 250V
 NEMA 6-15P
 UL CSA



20A 250V
 NEMA 6-20P
 UL CSA