

QBL22200

MOLDED CASE CIRCUIT BREAKER 240V 200A



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Product or component type	Molded Case Circuit Breaker
Range of product	PowerPact Q
[In] rated current	200 A
Product certifications	CSA IEC UL listed
[Ue] rated operational voltage	240 V AC
Mounting mode	Unit mount
Poles description	2P
Breaking capacity	10 kA 240 V AC
Electrical connection	Lugs line 4...300 AWG/kcmil aluminium/copper Lugs load 4...300 AWG/kcmil aluminium/copper
Trip unit technology	Thermal-magnetic
Magnetic hold current	1200 A
Magnetic tripping current	2400 A

Ordering and shipping details

Category	00005 - QO,Q2L 2P ENCL & BREAKERS
Discount Schedule	DE2A
GTIN	00785901412632
Nbr. of units in pkg.	1
Package weight(Lbs)	3.43
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.