

by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main Commercial Status Commercialised Product or component Load Center type Range of product QO Load center type Convertible Mains (breaker) [In] rated current 100 A Number of spaces 12 Short-circuit current 22 kA Number of circuits 12 Number of tandem 0 circuit breakers Network number of 1 phase phases [Ue] rated operational 120/240 V AC

Complementary

Complementary	
AWG gauge	62/0 AWG aluminium/copper
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated copper busbar
Product certifications	UL listed

voltage

Ordering and shipping details

Category	00002 - QO 1PH LC,12-42 CKT,NEMA3R	
Discount Schedule	DE3A	
GTIN	00785901867876	
Nbr. of units in pkg.	1	
Package weight(Lbs)	21.88	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

oner outlandsmy		
Sustainable offer status	Not Green Premium product	
RoHS	Will be Compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Period	18 months