


Straight Blade Devices
50 Ampere, 125/250 Volts, 3Ø 250 and 120/208 Volts AC
3 Pole, 4 Wire Grounding and 4 Pole, 4 Wire Non-Grounding
Single Receptacles and Plugs



HBL9450A

50A, 125/250V
3 Pole, 4 Wire Grounding
Receptacles and Plugs

IP20
SUITABILITY



50A 125/250V
NEMA 14-50R
 UL CSA
 3(2) HP



50A 125/250V
NEMA 14-50P
 UL CSA
 3(2) HP

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL9450A
Plug, nylon.	.625"-1.310" (15.9-33.3)	-
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	HBL9452C



HBL9451C

50A, 3Ø 250V AC
3 Pole, 4 Wire Grounding
Receptacles and Plugs

IP20
SUITABILITY




50A 3Ø 250V AC
NEMA 15-50R
 UL CSA
 7.5 HP




50A 3Ø 250V AC
NEMA 15-50P
 UL CSA
 7.5 HP

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL8450A
Plug, nylon.	.625"-1.310" (15.9-33.3)	-
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	HBL8452C



HBL9452C

 **50A, 3ØY 120/208V AC**
4 Pole, 4 Wire Non-Grounding
Receptacles and Plugs


IP20
SUITABILITY



50A 3ØY
120/208V AC
NEMA 18-50R
 UL Listed
 7.5 HP



50A 3ØY
120/208V AC
NEMA 18-50P
 UL Listed
 7.5 HP



HBL8350A

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL8350A
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-
		HBL8352C

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.
 See page A-49 for accessories.*