



## Straight Blade Devices

### Accessories

For 15 and 20 Ampere, 125 and 250 Volts and 277 Volts AC Devices



**IP44**  
SUITABILITY

#### Weatherproof Covers For Nylon Flanged Inlets and Flanged Receptacles

Description	Catalog Number
RTP, gray, for FS/FD box mounting.	<b>WP1</b>

Note: RTP is an abbreviation for reinforced thermoplastic polyester.  
See Section K, page K-24 for more information..



**WP1**

**IP55\***  
SUITABILITY

#### Weatherproof Boots

Description	Catalog Number
Seal-Tite® triple seal, black elastomer cover for Insulgrip® plugs (HBL5266C style), when used in a cord set, and connector bodies (HBL5269C style), when used with flanged inlets.	<b>HBL6017</b>
Same as above except yellow.	<b>HBL60CM17</b>
Seal-Tite® triple seal black elastomer cover for Insulgrip® connector bodies when used in a cord set.	<b>HBL6018</b>
Same as above except yellow.	<b>HBL60CM18</b>
Closure plug, black.	<b>HBL6019</b>
Closure plug, yellow.	<b>HBL60CM19</b>

Note: \* IP55 when installed and used properly with mating components.  
Boots are not UL Listed or CSA Certified.

**HBL6017**

**HBL6018**



**HBL60CM19**  
Shown with HBL6018

#### PLUGOUT® Device

Description	Catalog Number
Electrical plug lockout devices for 15 and 20A straight blade plugs.	<b>HLDMP**</b>
PLUGOUT® Lockout device for 20 and 30A Hubbell plugs and others.	<b>HLD**</b>

Note: \*\* Not UL Listed or CSA Certified.  
See Section U for complete details on lockout devices.



**HLDMP**

#### Inserts

Description	Catalog Number
Replacement cord grip inserts for Valise® device, (bag of 40).	<b>HBLVCGBK**</b>

Note: \*\* Not UL Listed or CSA Certified.



**HLD**