Product data sheet Characteristics

QO312L125G LOAD CENTER QO MLO 240V 125A 3PH 12SP



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main	
Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Fixed Mains (lugs)
[In] rated current	125 A
Number of spaces	12
Short-circuit current	65 kA
Number of circuits	12
Number of tandem circuit breakers	0
Network number of phases	3 phases
[Ue] rated operational voltage	240 V delta AC 240/120 V delta AC 208Y/120 V AC

Complementary

AWG gauge	62/0 AWG aluminium/copper	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Order separately	
Device composition	Grounding bar included (not installed)	
Electrical connection	Lugs	
Wiring configuration	3-wire 4-wire	
Material	Tin plated copper busbar	
Product certifications	UL listed	

Ordering and shipping details

00011 - QO 3PH LOAD CENTER,INDOOR	
DE3	
00785901295037	
1	
11.04	
Stock - Normally stocked in distribution facility	
Υ	
US	
	DE3 00785901295037 1 11.04 Stock - Normally stocked in distribution facility Y

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1248 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Period 18 months

