



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|-----------------------------------|---|
| Commercial Status | Commercialised |
| Product or component type | Load Center |
| Range of product | QO |
| Load center type | Convertible Mains (breaker) |
| [In] rated current | 100 A |
| Number of spaces | 27 |
| Short-circuit current | 25 kA |
| Number of circuits | 27 |
| Number of tandem circuit breakers | 0 |
| Network number of phases | 3 phases |
| [Ue] rated operational voltage | 240 V delta AC 240/120 V delta AC 208Y/120 V AC |

Complementary

| | |
|---------------------------|------------------------------------|
| AWG gauge | 4...2/0 AWG aluminium/copper |
| NEMA degree of protection | NEMA 1 indoor |
| Cover type | Order separately |
| Device composition | Grounding bar (ordered separately) |
| Electrical connection | Lugs |
| Wiring configuration | 3-wire 4-wire |
| Material | Tin plated copper busbar |
| Product certifications | UL listed |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 00011 - QO 3PH LOAD CENTER,INDOOR |
| Discount Schedule | DE3 |
| GTIN | 00785901295464 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 17.97 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Will be Compliant on 3Q2014 |
| REACH | Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|
