



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



### Main

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Fixed Mains (lugs)
[In] rated current	225 A
Number of spaces	42
Short-circuit current	65 kA
Number of circuits	42
Number of tandem circuit breakers	0
Network number of phases	3 phases
[Ue] rated operational voltage	240 V delta AC 240/120 V delta AC 208Y/120 V AC

### Complementary

AWG gauge	6...300 AWG/kcmil aluminium/copper
NEMA degree of protection	NEMA 1 indoor
Cover type	Order separately
Device composition	Grounding bar included (not installed)
Electrical connection	Lugs
Wiring configuration	3-wire 4-wire
Material	Tin plated copper busbar
Product certifications	UL listed

### Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901295532
Nbr. of units in pkg.	1
Package weight(Lbs)	20.96
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1248 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

---

Period	18 months
--------	-----------

---