Product data sheet Characteristics

QO342MQ150 LOAD CENTER QO MB 150A 3PH 42 CIRCUIT



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Convertible Mains (breaker)
[In] rated current	150 A
Number of spaces	42
Short-circuit current	25 kA
Number of circuits	42
Number of tandem circuit breakers	0
Network number of phases	3 phases
[Ue] rated operational voltage	240 V delta AC 240/120 V delta AC 208Y/120 V AC

Complementary

AWG gauge	4300 AWG/kcmil aluminium/copper	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Order separately	
Device composition	Grounding bar (ordered separately)	
Electrical connection	Lugs	
Wiring configuration	3-wire 4-wire	
Material	Tin plated copper busbar	
Product certifications	UL listed - CE marked	

Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR	
Discount Schedule	DE3	
GTIN	00785901290551	
Nbr. of units in pkg.	1	
Package weight(Lbs)	26.62	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Period 18 months

