



Twist-Lock® Devices
20 Ampere, 250 Volts
 2 Pole, 2 Wire, Non-Grounding
Insulgrip® Plugs, Flanged Inlets,
Connector Bodies and Receptacles



20A 250V
 NEMA L2-20P
 UL Listed
 2 HP

Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon, polarized. Multiple drive screws.	.220"-.720" (5.6-18.3)	HBL7102C

Accessories on page B-49.

Flanged Inlets

Description	Catalog Number
Nylon casing, back wired, polarized. Multiple drive screws.	HBL8815C

Accessories on page B-48.



20A 250V
 NEMA L2-20R
 UL Listed
 2 HP

Connector Bodies

Description	Cord Dia.	Catalog Number
Black and white nylon. Multiple drive screws.	.220"-.720" (5.6-18.3)	HBL7101C

Accessories on page B-49.

Receptacles

Description	Catalog Number
Single, black phenolic.	HBL7210B
Single, mounted on 4" (101.6) round box cover, black phenolic.	HBL7217B

Accessories on pages B-48 and B-49.

Flanged Receptacles


Description	Catalog Number
Insulgrip nylon casing, back wired. Multiple drive screws.	HBL8809C
Metal flange, stainless steel casing, black phenolic, exposed terminals.	HBL3226

Accessories on pages B-48 and B-49.

Note: Only receptacles and plugs are HP rated.
 HP ratings are AC only.




HBL7102C




HBL8815C




HBL7101C



HBL7210B



HBL8809C



HBL3226