

QO403L60NS

LOAD CENTER QO MLO 240V 60A 3PH 3SP N1



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Fixed Mains (lugs)
[In] rated current	60 A
Number of spaces	3
Short-circuit current	65 kA
Number of circuits	3
Number of tandem circuit breakers	0
Network number of phases	3 phases
[Ue] rated operational voltage	240 V delta AC 240/120 V delta AC 208Y/120 V AC

Complementary

AWG gauge	10...6 AWG copper
NEMA degree of protection	NEMA 1 indoor
Cover type	Surface cover
Device composition	Neutral (factory installed)
Electrical connection	Lugs
Wiring configuration	3-wire 4-wire
Material	Tin plated copper busbar
Product certifications	UL listed

Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901051701
Nbr. of units in pkg.	1
Package weight(Lbs)	5.75
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1248 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------
