

Product data sheet

Characteristics

QO816L100DS

LOAD CENTER QO MLO 240V 100A 1PH 8SP
N1



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Fixed Mains (lugs)
[In] rated current	100 A
Number of spaces	8
Short-circuit current	10 kA
Number of circuits	16
Number of tandem circuit breakers	8
Network number of phases	1 phase
[Ue] rated operational voltage	120/240 V AC

Complementary

AWG gauge	8...1 AWG aluminium/copper
NEMA degree of protection	NEMA 1 indoor
Cover type	Surface cover with door
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Product certifications	UL listed

Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901785743
Nbr. of units in pkg.	1
Package weight(Lbs)	8.38
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------