



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

### Main

Commercial Status	Commercialised
Product or component type	Miniature Circuit Breaker
Range of product	QO
[In] rated current	100 A
Product certifications	CSA UL listed
[Ue] rated operational voltage	240 V AC
Mounting mode	Bolt-on
Poles description	3P
Short-circuit current	22 kA
Number of spaces required	3
Circuit breaker type	Standard
Circuit breaker application	Not rated
Electrical connection	Box lugs
AWG gauge	4...2/0 AWG aluminium 4...2/0 AWG copper
Accessory / separate part type	None

### Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	00785901054801
Nbr. of units in pkg.	1
Package weight(Lbs)	1.06
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

### Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.