



# Twist-Lock® Devices

## 30 Ampere, 125/250 and 3Ø 250 Volts AC

3 Pole, 4 Wire Grounding

### Insulgrip® Connector Bodies and Receptacles



30A 125/250V AC  
NEMA L14-30R  
UL/CSA  
2 (2) HP



30A 3Ø 250V AC  
NEMA L15-30R  
UL/CSA  
3 HP

## Connector Bodies

Watertight Safety-Shroud®		IP66 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	HBL2713SW	HBL2723SW
Insulgrip®		IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	HBL2713	HBL2723
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL27CM13	HBL27CM23
All black nylon.	.350"-1.150" (9-29)	HBL2713BK	-

Accessories on page B-53.



HBL2713SW



HBL2713

## Receptacles

Watertight Safety-Shroud®, Back Wired		IP66 SUITABILITY	
Description	Catalog Number		
Gray Valox® housing and flange.	HBL2710SW	HBL2720SW	
Safety-Shroud® Twist-Lock®, Back Wired		IP20 SUITABILITY	
Description	Catalog Number		
Gray Valox® angle housing, one gang.	HBL2710AR	HBL2720AR	
Gray Valox® surface mounting, one gang.	HBL2710SR	HBL2720SR	
Gray Valox® semi-flush, two gang.	HBL2710SR2	HBL2720SR2	

Accessories on page B-54.



HBL2710SW

Single Flush, Back and Side Wired		IP20 SUITABILITY	
Description	Catalog Number		
Black nylon face.	HBL2710	HBL2720	
Isolated ground, orange nylon face.	IG2710	IG2720	
Ring terminal connection.	HBL2710RT	HBL2720RT	

Accessories on page B-52.



HBL2710AR


## Insulgrip® Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	HBL2716	HBL2726


Accessories on page B-52.



HBL2716



HBL2710



HBL2710SR2



HBL2710SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

