


Twist-Lock® Devices  
**30 Ampere, 3Ø 480 and 3Ø 600 Volts AC**  
 3 Pole, 4 Wire Grounding  
 Insulgrip® Plugs and Flanged Inlets



HBL2731SW




HBL2731S



HBL2731



HBL2735SW



HBL2735

**Plugs**

**Watertight Safety-Shroud®**

Description	Cord Dia.	IP66 SUITABILITY	
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	HBL2731SW	HBL2741SW

**Safety-Shroud®**

Description	Cord Dia.	IP20 SUITABILITY	
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.350"-1.150" (9-29)	HBL2731S	HBL2741S

Accessories on page B-40.

**Insulgrip®**

Description	Cord Dia.	IP20 SUITABILITY	
Black and white nylon.	.350"-1.150" (9-29)	HBL2731	HBL2741
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL27CM31	HBL27CM41

Accessories on page B-53.

**Flanged Inlets**

**Watertight Safety-Shroud®**

Description	IP66 SUITABILITY	
Gray Valox® housing and flange.	HBL2735SW	HBL2745SW

Accessories on page B-54.

**Insulgrip®**

Description	IP20 SUITABILITY	
Nylon casing, back wired.	HBL2735	HBL2745

Accessories on page B-52.

Note: For technical information on Twist-Lock and Watertight Safety-Shroud devices see pages B-69 and B-70.



HBLMITL - For use with Watertight Safety-Shroud receptacles, see page B-39.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.