



Twist-Lock® Devices
30 Ampere, 3ØY 120/208, 277/480 and 347/600 Volts AC
 4 Pole, 4 Wire Non-Grounding
**Insulgrip® Plugs, Flanged Inlets,
 Connector Bodies and Receptacles**



HBL2751


IP20
SUITABILITY



**30A 3ØY
120/208V AC
NEMA L18-30P
UL Listed
3 HP**



**30A 3ØY
277/480V AC
NEMA L19-30P
UL Listed
10 HP**




**30A 3ØY
347/600V AC
NEMA L20-30P
UL Listed**

Plugs

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2751	HBL2761	HBL2771

Accessories on page B-53.



HBL2755

Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	HBL2755	HBL2765	HBL2775

Accessories on page B-52.




HBL2753


IP20
SUITABILITY



**30A 3ØY
120/208V AC
NEMA L18-30R
UL Listed
3 HP**



**30A 3ØY
277/480V AC
NEMA L19-30R
UL Listed
10 HP**




**30A 3ØY
347/600V AC
NEMA L20-30R
UL Listed**

Connector Bodies

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2753	HBL2763	HBL2773

Accessories on page B-53.



HBL2750

Single Flush Receptacles, Back and Side Wired


Description	Catalog Number		
Black nylon face.	HBL2750	HBL2760	HBL2770

Accessories on page B-52.

Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2756	HBL2766	HBL2776

Accessories on page B-52.



HBL2756

Note: For technical information on Twist-Lock Devices see page B-69.