



# Non-NEMA Twist-Lock® Devices



## 10 Ampere, 250 Volts, 15 Ampere 125 Volts

3 Pole, 3 Wire and 2 Pole, 3 Wire

### Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles

For Replacement Use Only

**IP20**  
SUITABILITY



**HBL7567C**


## Plugs

| Description                                       | Cord Dia.                | Catalog Number   |   |
|---|--------------------------|------------------|---|
| Black and white nylon.<br>Multiple drive screws.  | 230"-.720"<br>(5.8-18.3) | <b>HBL7567C</b>  | - |
| Yellow and white nylon.<br>Multiple drive screws. | 230"-.720"<br>(5.8-18.3) | <b>HBL7567CY</b> | - |

Accessories on page B-49.


## Flanged Inlets

| Description             | Catalog Number |                 |
|-------------------------|----------------|-----------------|
| Stainless steel casing. | <b>HBL7556</b> | <b>HBL7556G</b> |



**HBL7556**


**IP20**  
SUITABILITY



## Connector Bodies

| Description   | Cord Dia.                 | Catalog Number   |                 |
|---|---------------------------|------------------|-----------------|
| Insulgrip connector,<br>black and white nylon.<br>Multiple drive screws.  | 230"-.720"<br>(5.8-18.3)  | <b>HBL7565C</b>  | -               |
| Insulgrip connector,<br>yellow and white nylon.<br>Multiple drive screws. | 230"-.720"<br>(5.8-18.3)  | <b>HBL7565CY</b> | -               |
| Black phenolic.   | .296"-.625"<br>(7.5-15.9) | <b>HBL7555</b>   | <b>HBL7555G</b> |

Accessories on page B-49.




**HBL7565C**

## Receptacles

| Description             | Catalog Number |                 |
|-------------------------|----------------|-----------------|
| Duplex, black RTP*.     | <b>HBL7580</b> | <b>HBL7580G</b> |
| Single, black phenolic. | <b>HBL7582</b> | <b>HBL7582G</b> |

Accessories on page B-48.




**HBL7580**

## Flanged Receptacles

| Description             | Catalog Number |                 |
|-------------------------|----------------|-----------------|
| Stainless steel casing. | <b>HBL7557</b> | <b>HBL7557G</b> |

Accessories on page B-49.



**HBL7557**

Note: \* RTP is an abbreviation for reinforced thermoplastic.  
The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

**CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.**