




Non-NEMA Twist-Lock® Devices 20 Ampere, 250, 125/250 Volts and 3ØY 120/208 Volts AC Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles

For Replacement Use Only

IP20
SUITABILITY



2P 3W
20A 250V
Non-NEMA
Not UL Listed



3P 3W
20A 125/250V
Non-NEMA
Not UL Listed

Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.360"-.930" (9-24)	HBL7314GCB	HBL7314C
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	-	HBL73CM14C

Accessories on page B-51.




HBL7314C

Single Flush Receptacles

Description	Catalog Number	
Black nylon face, back wired.	HBL7310BG	HBL7310B

Accessories on page B-50.




HBL7310B

Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	-	HBL3326C


Accessories on page B-50.



HBL3326C

For Replacement Use Only

IP20
SUITABILITY



3P 4W
20A 3Ø 250V AC
Non-NEMA
Not UL Listed



4P 4W
20A 3Ø Y
120/208V AC
Non-NEMA
Not UL Listed

Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	HBL7413GCB	HBL7413C

Accessories on page B-53.




HBL7413GCB

Single Flush Receptacles

Description	Catalog Number	
Black urea face, back wired.	HBL7410BG	HBL7410B
Mounted on a 4" (101.6) round metal cover.	-	HBL7417B

Accessories on page B-52.




HBL7410BG

Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	-	HBL7409C

Accessories on page B-52.



HBL7409C

Note: The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.