for 15 Ampere 2 and 3 Wire Plugs, Connector Bodies and Flanged Devices



Compact 2-gang design

#### **Pool Kit Contains:**

- · Heavy duty, industrial grade locking receptacle (NEMA L5-20, 20A 125V or NEMA L6-20, 20A 250V)
- Single-pole or double-pole switch (20A, 120-277V AC)
- Two gang, 2 inch deep die-cast aluminum weatherproof box with (4) 3/4 inch threaded outlets
- Two gang, weatherproof while-in-use cover
- Includes mounting hardware, gasket, wire connector and (3) closure plugs
- Complete assembly instructions

HBLPKL520

IP55\*

Description	
Pool pump	receptacle kit.

## Weatherproof, Seal-Tite®, Triple Seal Boots for 15A Insularin® Devices

Tor Tor Insuignp Devices		
Description	Catalog Number	
Black elastomer boot for plugs when used in a cord set and connector bodies when used with a flange inlet.	HBL6023	
Same as above except yellow elastomer.	HBL60CM23	
Black elastomer boot for connector bodies when used in cord sets.	HBL6024	
Same as above except yellow elastomer.	HBL60CM24	

Note: \* When installed and used properly with plug and connector body combinations.


## **Closure Cover**

Description	Catalog Number
For use with 3 wire 15A Twist-Lock flush or flanged receptacles.	HBL7529A

# PLUGOUT<sup>®</sup> Lockout Devices

Description	Catalog Number
Lockout device for 15A and 20A straight blade plugs.	HLDMP
Lockout device for attachable 20 and 30A plugs, straight body or angle types, with or without weatherproof covers.	HLD

Note: See Section U for more information on PLUGOUT Lockout Devices.



HLDMP



HBL6023



HBL6024



HBL7529A



