




# Twist-Lock® Devices

## 15 Ampere, 125 and 125/250 Volts

### Midget Twist-Lock® Connector Bodies and Flanged Receptacles

**IP20**  
SUITABILITY



## Connector Bodies

Description	Cord Dia.	Catalog Number		
Valise® connector body, black nylon, polarized.	.220"-.385" (5.6-9.8)	<b>HBL7464V</b>	-	-
Valise® connector body, black nylon, insulation displacement terminals.	.300"-.430" (7.6-10.9)	-	<b>HBL7593V</b>	-
Black nylon cover, phenolic body, screw terminals.	.281"-.421" (7.1-10.7)	-	<b>HBL7593</b>	-
Angle connector body, black nylon cover, phenolic body, screw terminals.	.335"-.421" (8.5-10.7)	-	<b>HBL7571</b>	-
Valise® type, black nylon, with insulation displacement terminals, multiple drive screws.	.300"-.430" (7.6-10.9)	-	-	<b>HBL7484V</b>
Black nylon body, phenolic base, multiple drive screws, cord grip.	.281"-.421" (7.1-10.7)	-	-	<b>HBL7484</b>
Same as above, except for angle cord grip.	.335"-.421" (8.5-10.7)	-	-	<b>HBL7433</b>


Accessories on page B-6.

## Flanged Receptacles


Description	Catalog Number		
Stainless steel flange, exposed terminals.	<b>HBL7468</b>	-	-
Exposed terminals, black nylon flange.	-	<b>HBL7596N</b>	-
Exposed terminals, stainless steel flange.	-	<b>HBL7596</b>	-
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in dia.	-	<b>HBL7598</b>	-
Exposed terminals, black nylon flange.	-	-	<b>HBL7487N</b>
Exposed terminals, stainless steel flange.	-	-	<b>HBL7487</b>
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in diameter.	-	-	<b>HBL7489</b>

Accessories on page B-6.

Note: Male ML-2R devices have solid center ground pins.  
Male ML-3R devices have hollow center neutral sleeves.



**HBL7464V**




**HBL7593V**



**HBL7593**




**HBL7571**



**HBL7484V**




**HBL7484**




**HBL7596**



**HBL7598**



**HBL7596N**



**HBL7468**

