Weatherproof, Seal-Tite®, Triple Seal Boots

or when used with flush receptacles or connector bodies when used with flanged inlets. Black elastomer.

Nylon, angle adapter for Insulgrip plugs and connectors,

Seal-Tite® triple seal cover for plug when used on a cord set

Seal-Tite triple seal cover for connector bodies, when used on

for 20 and 30 Ampere, 4 and 5 Wire Plugs and Connector Bodies



「wist-Lock[®] Devices

CT.	110
	-110
12	

HBL6035



HBL6036



HBL45WAA



HLD



	1
Catalog Number	
HBL45WAA	

Catalog Number

HBL60CM35

HBL60CM36

HBL6035

HBL6036

PLUGOUT[®] Lockout Device

cord grip range .350"-1.15" (8.9-29.2).

Insulgrip[®]

Same as above except yellow.

Same as above except yellow.

Angle Adapter

Description

interconnecting cord sets. Black elastomer.

Description

Description	Catalog Number
Lockout device for attachable 20 and 30A plugs, straight body or angle types, with or without weatherproof covers.	HLD
Lockout device for 20 and 30A, 4 and 5 wire angle plugs and watertight Safety-Shroud [®] Twist-Lock plugs.	HLD2

Note: See Section U for more information on PLUGOUT Lockout Devices. * When installed and used properly, with plug and connector body combinations.

Insulgrip® Plug and Connector Body Latching Kit

When you want to make doubly sure that plugs and connector bodies stay connected, the Hubbell latching kit provides both improved safety and security through a double locking feature that makes unintentional disconnection virtually impossible – even under high vibration situations. The plug and connector body lock once when first connected, then again when you push the special position locking slide into place.

Insulgrip[®] Latching Kit

Description	Catalog Number
For all 20 and 30A, 4 and 5 wire Twist-Lock Insulgrip plugs	SK3
and connectors.	



SK3



