





Twist-Lock® Devices

50 Ampere, 250 Volts DC and 600 Volts AC

3 Pole, 4 Wire Grounding

Plugs, Flanged Inlets, Connector Bodies and Receptacles

 **Important Note:** Catalog numbers *HBL7379, HBL7764C, HBL7765C, HBL7958, HBL7968* are for replacement use only. See other singly rated 50A Twist-Lock® devices in this section. *HBL3700 series Twist-Lock devices do not interchange with any other devices in this section.*






Plugs

| Description | Cord Dia. | Catalog Number | |
|--|-------------------------------|-----------------|-----------------|
| Nylon cover, thermoplastic polyester interior. | .830"-1.250" (21.08-31.75) | HBL3765C | HBL7765C |

Accessories on page B-60.



HBL3765C

Flanged Inlets

| Description | Catalog Number | |
|---|----------------|----------------|
| Zinc plated steel casing, thermoset interior. | HBL3775 | HBL7958 |
| Zinc plated steel casing, thermoset interior with lift cover. | HBL3768 | HBL7968 |





HBL3768

Connector Bodies

| Description | Cord Dia. | Catalog Number | |
|--|-------------------------------|-----------------|-----------------|
| Nylon cover, thermoplastic polyester interior. | .830"-1.250" (21.08-31.75) | HBL3764C | HBL7764C |

Accessories on page B-60.




HBL3775


Receptacles

| Description | Catalog Number | |
|-----------------|----------------|----------------|
| Black melamine. | HBL3769 | HBL7379 |

Accessories on page B-60.



HBL3764C



HBL3769

