

### Corrugated Loom Tubing – Slit

- Provides protection for cables
- Packaged on a reel for easy handling and dispensing of product

- For indoor use only
- Material: Polyethylene
- Temperature Range: -40°F to 122°F (-40°C to 50°C)



Part Number	Color	Inside Diameter		Outside Diameter		Length of Reel‡		Std. Pkg. Qty.*
		In.	mm	In.	mm	Ft.	m	
<b>Slit Wall</b>								
<b>CLT25F-C3</b>	Orange	0.28	7.0	0.40	10.1	100	30.5	1
<b>CLT38F-C3</b>	Orange	0.42	10.5	0.56	14.1	100	30.5	1
<b>CLT50F-C3</b>	Orange	0.51	12.8	0.67	17.0	100	30.5	1
<b>CLT75F-C3</b>	Orange	0.76	19.3	0.94	23.8	100	30.5	1
<b>CLT100F-C3</b>	Orange	0.92	23.2	1.09	27.7	100	30.5	1
<b>CLT125F-L3</b>	Orange	1.29	32.8	1.50	38.1	50	15.2	1
<b>CLT150F-X3</b>	Orange	1.48	37.6	1.73	43.9	10	3.1	1
<b>CLT188F-X3</b>	Orange	1.88	47.8	2.17	55.1	10	3.1	1
<b>CLT25F-C20</b>	Black	0.28	7.0	0.40	10.1	100	30.5	1
<b>CLT38F-C20</b>	Black	0.42	10.5	0.56	14.1	100	30.5	1
<b>CLT50F-C20</b>	Black	0.51	12.8	0.67	17.0	100	30.5	1
<b>CLT75F-C20</b>	Black	0.76	19.3	0.94	23.8	100	30.5	1
<b>CLT100F-C20</b>	Black	0.92	23.2	1.09	27.7	100	30.5	1
<b>CLT125F-L20</b>	Black	1.29	32.8	1.50	38.1	50	15.2	1
<b>CLT150F-T20</b>	Black	1.48	37.6	1.73	43.9	200	61.0	1
<b>CLT150F-X20</b>	Black	1.48	37.6	1.73	43.9	10	3.0	1
<b>CLT188F-X20</b>	Black	1.88	47.8	2.17	55.1	10	3.1	1
<b>CLT150F-X4</b>	Yellow	1.48	37.6	1.73	43.9	10	3.1	1
<b>CLT188F-X4</b>	Yellow	1.88	47.8	2.17	55.1	10	3.1	1
<b>Solid Wall</b>								
<b>CLTS25F-C3</b>	Orange	0.28	7.0	0.40	10.1	100	30.5	1
<b>CLTS38F-C3</b>	Orange	0.42	10.5	0.56	14.1	100	30.5	1
<b>CLTS50F-C3</b>	Orange	0.51	12.8	0.67	17.0	100	30.5	1
<b>CLTS75F-C3</b>	Orange	0.76	19.3	0.94	23.8	100	30.5	1
<b>CLTS100F-C3</b>	Orange	0.92	23.2	1.09	27.7	100	30.5	1
<b>CLTS125F-L3</b>	Orange	1.29	32.8	1.50	38.1	50	15.2	1
<b>CLTS150F-D3</b>	Orange	1.48	37.6	1.73	43.9	500	152.4	1
<b>CLTS25F-C</b>	Black	0.28	7.0	0.40	10.1	100	30.5	1
<b>CLTS38F-C</b>	Black	0.42	10.5	0.56	14.1	100	30.5	1
<b>CLTS50F-C</b>	Black	0.51	12.8	0.67	17.0	100	30.5	1
<b>CLTS75F-C</b>	Black	0.76	19.3	0.94	23.8	100	30.5	1
<b>CLTS100F-C</b>	Black	0.92	23.2	1.09	27.7	100	30.5	1
<b>CLTS125F-L</b>	Black	1.29	32.8	1.50	38.1	50	15.2	1

‡Reel packaging may contain splices.

\*Order number of reels required.

Contact Panduit Customer Service for additional sizes, materials, colors and bulk packaging.