

1/4" DRIVE DEEP LENGTH SOCKETS - 12 POINT

- Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.

1/4" DRIVE DEEP LENGTH SOCKETS - 12 POINT



Product ID No.	 in.	B	C	D	E	L	Weight lbs.	ASME Spec.	AS Spec.
J4706LT	3/16"	5/16"	27/64"	9/32"	1-5/32"	2"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
J4707LT	7/32"	11/32"	27/64"	3/8"	1-5/32"	2"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
J4708LT	1/4"	3/8"	27/64"	3/8"	1-5/32"	2"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
J4709LT	9/32"	27/64"	27/64"	3/8"	1-5/32"	2"	0.05 lbs.	ASME B107.1	AS954E S3.8.1
J4710LT	5/16"	29/64"	29/64"	3/8"	1-5/32"	2"	0.06 lbs.	ASME B107.1	AS954E S3.8.1
J4711LT	11/32"	1/2"	1/2"	5/8"	1-5/32"	2"	0.07 lbs.	ASME B107.1	AS954E S3.8.1
J4712LT	3/8"	35/64"	35/64"	5/8"	1-5/32"	2"	0.07 lbs.	ASME B107.1	AS954E S3.8.1
J4714LT	7/16"	39/64"	39/64"	5/8"	1-5/32"	2"	0.10 lbs.	ASME B107.1	AS954E S3.8.1
J4716LT	1/2"	11/16"	11/16"	5/8"	1-5/32"	2"	0.12 lbs.	ASME B107.1	AS954E S3.8.1
J4718LT	9/16"	3/4"	3/4"	5/8"	1-5/32"	2"	0.13 lbs.	ASME B107.1	AS954E S3.8.1



1/4" DRIVE METRIC DEEP LENGTH SOCKETS - 12 POINT

METRIC



Product ID No.	 mm	B	C	D	E	L	Weight lbs.	ASME Spec.	AS Spec.
J4705LTM	5	7.9	11.7	7.0	19.5	50.5	0.05 lbs.	ASME B107.5M	AS954E S3.8.1
J47055LTM	5.5	8.8	11.7	7.0	19.5	50.5	0.05 lbs.	ASME B107.5M	AS954E S3.8.1
J4706LTM	6	9.4	11.7	9.5	19.5	50.5	0.05 lbs.	ASME B107.5M	AS954E S3.8.1
J4707LTM	7	10.8	11.7	9.5	19.5	50.5	0.07 lbs.	ASME B107.5M	AS954E S3.8.1
J4708LTM	8	11.7	11.7	9.5	19.5	50.5	0.06 lbs.	ASME B107.5M	AS954E S3.8.1
J4709LTM	9	12.7	12.7	16.0	36.5	50.5	0.06 lbs.	ASME B107.5M	AS954E S3.8.1
J4710LTM	10	14.4	14.4	16.0	36.5	50.5	0.08 lbs.	ASME B107.5M	AS954E S3.8.1
J4711LTM	11	15.6	15.6	16.0	36.5	50.5	0.09 lbs.	ASME B107.5M	AS954E S3.8.1
J4712LTM	12	16.5	16.5	16.0	36.5	50.5	0.10 lbs.	ASME B107.5M	AS954E S3.8.1
J4713LTM	13	17.6	17.6	16.0	36.5	50.5	0.11 lbs.	ASME B107.5M	AS954E S3.8.1
J4714LTM	14	19.6	19.6	16.0	36.5	50.5	0.13 lbs.	ASME B107.5M	AS954E S3.8.1
J4715LTM	15	21.4	21.4	16.0	36.5	50.5	0.20 lbs.	ASME B107.5M	AS954E S3.8.1

