



EFX[®] Solvent Degreaser



FEATURES

- Ideal for cleaning electrical/electronic parts
- Instant degreasing action
- Quickly removes grease and oil
- Power blast spray
- Fast evaporating
- Safe to use on most surfaces
- Ideal for cleaning metals and most plastics
- No residue
- Non-chlorinated



PACKAGE SIZES

Net Contents	Part No.
15 wt. oz./425 g/ 588 mL	01820
5 gal. (18.93 L)	01805

APPLICATIONS

- Air Compressors
- Circuit Breakers
- Electric Motors
- Electronic Connectors
- Hinges
- Engines
- Forklifts
- Ignition Systems
- Power Tools
- Relays
- Switch Gears



EFX[®] SOLVENT DEGREASER

PROPERTIES

Appearance/physical state	Liquid	Color	Colorless
Odor	Characteristic	Partition coefficient	> 1 (n-octanol/water)
KB value	≥ 48	Flash point °F(°C)	21 °F (-6°C)
Boiling/Condensation point °F(°C)	140.9 °F (60.5 °C)	Flash point method	Tag Closed Cup
Heat of combustion	> 30 kJ/g	Auto-ignition temperature	582.8°F (306°C)
VOC	86.9% per US State and Federal Consumer Product Regulations	Viscosity	< 3 cSt @ 25°C
Flammable limits (estimated)	lower= 1.5% upper= 9%	Solubility in water	< 10%
Evaporation Rate	1.6 (water=1)	Percent volatile	100%
Vapor density	~ 2.8	Specific gravity	0.65 - 0.68 @ 20°C
Type propellant	Carbon Dioxide		

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

DIRECTIONS

Spray on parts and equipment. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 122°F/50°C. Do not puncture, incinerate or crush. Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM



4647 Hugh Howell Road • Tucker, GA 30084
 TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899
 WEB SITE: www.lpslabs.com

©2015 ITW Pro Brands • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • TDS_01820 • 151013