

Heavy-Duty Air Circulators - 115V

Pedestal, Wall, I-Beam & Ceiling Mount Fans Non-Oscillating



Adjustable Pedestal



Wall Mount

5 Year Warranty - Ultra Quiet

FEATURES

- Energy Efficient - Lowest Watts Per CFM, Ultra Quiet Die Cast Aluminum Airfoil Propeller
- Excellent for Churches, Schools, Industrial and Commercial Applications
- Includes Supply Cord and Plug, Wall and I-Beam Mounts
- Meets OSHA Standards, 3 Speed Motor, 26" Base (18" & 20"); 32" Base (24" & 30")
- 1/5 HP(18" & 20") and 1/3 HP(24" & 30"), 1 Phase, Totally Enclosed, Ball Bearing Motor
- Patented Modular Motor End Dome for easy maintenance, All Stocked

PERFORMANCE 115V

Prop Dia.	CFM			RPM			Motor Number	F.L. Amps
	High	Med.	Low	High	Med.	Low		
18"	2600	2113	1805	1125	915	780	642J (Non-Osc.)	1.41
20"	3100	2060	1657	1120	745	600	642J (Non-Osc.)	1.65
24"	5588	4556	3325	1110	900	700	642 (Non-Osc.)	2.5
30"	8402	6259	4463	1098	880	660	642 (Non-Osc.)	2.7

Performance Ratings are conducted in accordance with AMCA Standard 230-99.

Unit Packs, Models - 642 Motor

Motor, Specified Mounting, Propeller & Guard Shipped In A Single Carton



Ceiling Mount



I-Beam Mount

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.	List Price
20892	UP18LF16-S	18"	Pedestal Fan	1/5	65	\$723
20899	UP18LW16-S8	18"	Wall Mount	1/5	45	\$607
20906	UP18LI16-S	18"	I-Beam Mount	1/5	48	\$704
20911	UP18LS16-S	18"	Ceiling Mount	1/5	49	\$581
20893	UP20LF6-S	20"	Pedestal Fan	1/5	66	\$750
20902	UP20LW16-S8	20"	Wall Mount	1/5	46	\$642
20907	UP20LI16-S	20"	I-Beam Mount	1/5	49	\$742
20912	UP20LS16-S	20"	Ceiling Mount	1/5	50	\$617
20895	UP24LF16-S	24"	Pedestal Fan	1/3	85	\$983
37144	UP24LW16-S8	24"	Wall Mount	1/3	56	\$877
37139	UP24LI16-S	24"	I-Beam Mount	1/3	58	\$956
37137	UP24LS16-S	24"	Ceiling Mount	1/3	50	\$843
20900	UP30LF16-S	30"	Pedestal Fan	1/3	91	\$1,063
37145	UP30LW16-S8	30"	Wall Mount	1/3	60	\$955
37140	UP30LI16-S	30"	I-Beam Mount	1/3	63	\$1,034
37138	UP30LS16-S	30"	Ceiling Mount	1/3	55	\$937

MOTOR TILT ADJUSTMENTS

TYPE	TILT UP OR DOWN (IN DEGREES)			
	OSCILLATING		NON-OSCILLATING	
	UP	DOWN	UP	DOWN
FLOOR	20°	10°	20°	10°
WALL	20°	10°	20°	15°
I-BEAM	20°	20°	20°	20°

0° = Horizontal Plane

Ceiling Mount: A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

Assembled Fan Heads, Models - 642 Motor

Motor, Propeller & Guard Assembled

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Ship. Wt.	List Price
20115	M24GBA	24"	Head Assembly	1/3	41	\$798
20915	M30GBA	30"	Head Assembly	1/3	47	\$877

Mountings

For Fan Head Component Packs and Assembled Fan Heads

EDP No.	Catalog No.	Fan Style	Ship. Wt.	Description	List Price
21152	8CP2B	Adj. Pedestal	13	5' to 8' pedestal (for use with A786B base.)	\$125
21165	A-786B-1	Floor Base	17	For use with 8CP-2B pedestal on 18", 20", 26" and 32" fans.	\$116
21166	A786B-2	Floor Base	34	For use with 8CP-2B pedestal on 24", 26", 30" and 32" fans.	\$118
21187	878W	Wall Bracket	10	Use for HD air circulator wall mountings. Includes Safety Cable Kit.	\$127
21191	700-U	I-Beam Bracket	5	Use for HD air circulator I-Beam mountings. Includes Safety Cable Kit.	\$210
21203	CK-2	Ceiling Bracket	14	Use for HD air circulator ceiling mount (-non-oscillating only.) Extension pipe not included. Includes Safety Cable Kit.	\$92

NOTES: See Page 9 for optional accessories and component parts for fan head assemblies.