

# LC1F2100

contactor, TeSys F, 3P(3NO), AC-1, <=1000V  
AC 2100A with coil LX1/LX9, 110...500V AC  
40/400Hz, LX4, 110...440V DC



## Main

Range	TeSys
Product name	TeSys F
Product or Component Type	Contacteur
Device short name	LC1F
Contacteur application	Resistive load
Utilisation category	AC-1
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	2100 A 104 °F (40 °C) <= 440 V AC AC-1

## Complementary

[Uc] control circuit voltage	110...500 V AC 40...400 Hz with LX1/LX9 coil 110...440 V DC with LX4 coil
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	2100 A 104 °F (40 °C)
Irms rated making capacity	3150 A AC IEC 60947-4-1
Rated breaking capacity	3150 A power circuit IEC 60947-4-1
[Icw] rated short-time withstand current	10000 A 104 °F (40 °C) - 10 s power circuit 7500 A 104 °F (40 °C) - 30 s 5500 A 104 °F (40 °C) - 1 min 4200 A 104 °F (40 °C) - 3 min 3000 A 104 °F (40 °C) - 10 min
Associated fuse rating	2000 A gG <= 440 V power circuit IEC 60947-4-1
Average impedance	0.1 mOhm - Ith 2100 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C 1000 V UL 60947-4-1
Power dissipation per pole	200 W AC-1
Control circuit voltage limits	Operational: 0.85...1.1 Uc AC 40...400 Hz with LX1/LX9 coil Drop-out: 0.3...0.55 Uc AC 40...400 Hz with LX1/LX9 coil Operational: 0.85...1.1 Uc DC with LX4 coil Drop-out: 0.2...0.35 Uc DC with LX4 coil
Heat dissipation	18 W
Operating time	40...75 ms closing with LX1/LX9 coil 100...170 ms opening with LX1/LX9 coil 50...60 ms closing with LX4 coil 45...60 ms opening with LX4 coil
Mounting Support	Plate
Standards	JIS C8201-4-1 EN 60947-1 EN 60947-4-1 IEC 60947-4-1 IEC 60947-1 UL 60947-4-1 CSA C22.2 No 60947-4-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product Certifications	CCC UL CB Scheme CSA EAC UKCA
Connections - terminals	Power circuit bar 4 Power circuit bolted connection Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid without cable end Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )
Tightening torque	Power circuit 513.34 lbf.in (58 N.m) Control circuit 10.62 lbf.in (1.2 N.m)
Mechanical durability	0.5 Mcycles
Inrush power in VA	1600...2400 VA, 40...400 Hz cos phi 0.9 (at 68 °F (20 °C))with LX1/LX9 coil 2000...2200 VA (at 68 °F (20 °C))with LX4 coil
Hold-in power consumption in VA	29...37 VA, 40...400 Hz cos phi 0.9 (at 68 °F (20 °C))with LX1/LX9 coil 8...10 VA (at 68 °F (20 °C))with LX4 coil
Maximum operating rate	600 cyc/h 131 °F (55 °C)

## Environment

Protective treatment	TH
Ambient Air Temperature for Operation	23...104 °F (-5...40 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...140 °F (-40...60 °C)
Operating altitude	9842.52 ft (3000 m) without derating
Mechanical robustness	Vibrations contactor open2 Gn, 5...300 Hz Vibrations contactor closed4 Gn, 5...300 Hz Shocks contactor open6 Gn for 1/2 sine wave (11 ms) Shocks contactor closed15 Gn for 1/2 sine wave (11 ms)
Height	13.07 in (332 mm)
Width	17.24 in (438 mm)
Depth	9.39 in (238.6 mm)
Net Weight	68.34 lb(US) (31 kg)

## Ordering and shipping details

Category	22336-CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	I12
GTIN	3389118372658
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.96 in (38.0 cm)
Package 1 Width	19.69 in (50.0 cm)
Package 1 Length	23.62 in (60.0 cm)
Package 1 Weight	68.34 lb(US) (31.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------