


## 3/8" DRIVE TORX® IMPACT SOCKETS


- › Made of heat-treated alloy steel.
- › Socket size stamped on tool for easy identification.
- › Side locking hole.
- › For use with Torx® style fasteners.

Torx® Size		Overall Length (in)	Weight (lbs)
E6	<b>J7206TX</b>	1-1/4	0.06
E7	<b>J7207TX</b>	1-1/4	0.07
E8	<b>J7208TX</b>	1-1/4	0.07
E10	<b>J7210TX</b>	1-1/4	0.07
E12	<b>J7212TX</b>	1-1/4	0.07
E14	<b>J7214TX</b>	1-1/4	0.09
E16	<b>J7216TX</b>	1-1/4	0.10




## 3/8" DRIVE IMPACT HEX BIT SOCKETS

- › Proto® Hex Bit Impact Sockets can be used on stubborn fasteners.
- › Tight tolerances for snug fit on fastener.
- › Hex bit impact sockets are used wherever powered drive tools are used to install or remove fasteners.
- › Hex bit impact sockets are designed to withstand the high torque and force associated with impact tools in repetitive application.
- › Side locking hole.

INCH		Bit Length (in)	Overall Length (in)	Weight (lbs)
1/8	<b>J72901/8</b>	1-5/8	2-23/32	0.07
5/32	<b>J72905/32</b>	1-5/8	2-23/32	0.08
3/16	<b>J72903/16</b>	1-5/8	2-23/32	0.08
7/32	<b>J72907/32</b>	1-5/8	2-23/32	0.09
1/4	<b>J72901/4</b>	1-5/8	2-23/32	0.10
5/16	<b>J72905/16</b>	1-5/8	2-23/32	0.13
3/8	<b>J72903/8</b>	1-5/8	2-23/32	0.14



MM		Bit Length (in)	Overall Length (in)	Weight (lbs)
4	<b>J7290-4M</b>	1-5/8	2-23/32	0.07
5	<b>J7290-5M</b>	1-5/8	2-23/32	0.08
6	<b>J7290-6M</b>	1-5/8	2-23/32	0.09
8	<b>J7290-8M</b>	1-5/8	2-23/32	0.12
10	<b>J7290-10M</b>	1-5/8	2-23/32	0.14



Torx® is a trademark of Acument Intellectual Properties, LLC

Country of origin accurate at time of printing, consult [www.protoindustrial.com](http://www.protoindustrial.com) for updated information.