

## Non-Oscillating Unit Packs



Adjustable Floor Model



Non-Oscillating Ceiling Mount



Non-Oscillating Wall Mount

### 3 Year Warranty FEATURES

- 5 Mounting Options
- Guard Meets OSHA Standards
- 115V, 60 Hz, 1 Phase, 2 Speed, 1/15 HP (18" & 20") and 3 Speed, 1/3 HP (24" & 30"), Totally Enclosed Air Over Ball Bearing Motors
- Galvanized Steel Propeller
- 15 Foot Three Conductor Supply Cord and Plug
- All Stocked

All Parts Packaged in One UPS Shippable Carton

### NON-OSCILLATING PERFORMANCE 115V

Prop Dia.	CFM			RPM			Motor Number	F.L. Amps
	High	Med.	Low	High	Med.	Low		
18"	2520	---	1850	1480	---	1020	I-1820TEM	2.6
20"	2670	---	2035	1650	---	1240	I-1820TEM	2.6
24"	5520	4020	2820	1080	700	540	I-3A	3.0
30"	7185	5300	3415	1080	700	540	I-3A	3.0

Performance Ratings are conducted in accordance with AMCA Standard 230-99.



EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.	List Price
71760	UPI-24PA2A (3-SP)	24"	Adjustable Floor (S.B.)	1/3	81	\$646
71725	I-24W2A (3-SP)	24"	Wall/Ceiling Model	1/3	44	\$525
71526	UPI-30PA2A (3-SP)	30"	Adjustable Floor (S.B.)	1/3	90	\$685
71726	I-30W2A (3-SP)	30"	Wall/Ceiling Model	1/3	49	\$568

Unit Pack - Motor, specified Style Mounting, Propeller & Guard shipped in a single carton.  
S.B. = Solid Base

### MOTOR TILT ADJUSTMENTS

TYPE	TILT UP OR DOWN (IN DEGREES)	
	NON-OSCILLATING	
	UP	DOWN
FLOOR	30°	15°
WALL	30°	50°
I-BEAM	30°	15°
CEILING	0°	90°

0° = Horizontal Plane

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

### Non-Oscillating Assembled Fan Heads †



Industrial Head Assembly

EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	PH	Ship Wt.	List Price
37113	I-18TEHA	18"	Head Assembly	1/15*	1	24	\$325
37114	I-20TEHA	20"	Head Assembly	1/15*	1	27	\$339
37209	I-24-2	24"	Head Assembly	1/3	1	37	\$519
37212	I-30	30"	Head Assembly	1/3	1	48	\$561

† Motor, Guard, Propeller Pre-Assembled.

\* Motor is 2-speed.

\*\*30" Head Assembly is UPS OverSize 2.