


OB/SB-1




3" x 2" Square Corner Switch Boxes


With Nonmetallic Sheathed Cable Clamps




384LES-VB
2-1/2" Deep, Welded
Plain vertical bracket
set back 3/4"




384LES
2-1/2" Deep, Welded
Four nail holes
each side




384VB-PL2G
2-1/2" Deep, Welded
Plain vertical bracket
set back 3/4"




385-LES
2-1/2" Deep, Welded
External nail brackets




385-LESN
2-1/2" Deep, Welded
Two 16 penny nails
in side




389
2-3/4" Deep, Gangable
Plaster ears*




389VB
2-3/4" Deep, Gangable
Plain vertical bracket
set back 3/4"



384D
3-1/2" Deep, Gangable
Two nail holes each side
Plaster ears*




384DLE
3-1/2" Deep, Gangable
Two nail holes
each side



384D-NL
3-1/2" Deep, Gangable
Stud NL bracket
set back 1/2"

Catalog Number	Depth (inches)	Wiring Cubic Inch Capacity	Type Clamp	Knockout Sides	Description Ends	Bottom	Wt. Lbs. Per 100	Std. Pkg.
384LES-VB Non-Gangable	2-1/2	12.5	CL-26	--	(2)1/2"	(1)1/2"	66.0	50
384LES Non-Gangable	2-1/2	12.5	CL-26	--	(2)1/2"	(1)1/2"	61.0	50
384VB-PL2G Non-Gangable, Welded Assembly	2-1/2	25.0	CL-26	--	(2)1/2"	(2)1/2"	97.0	25
385-LES Non-Gangable	2-1/2	12.5	CL-26	--	(2)1/2"	(1)1/2"	64.0	50
385-LESN Non-Gangable	2-1/2	12.5	CL-26	--	(2)1/2"	(1)1/2"	67.0	50
389* Gangable	2-3/4	14.0	CL-26	(4)1/2"	(2)1/2"	(1)1/2"	68.0	50
389VB Gangable	2-3/4	14.0	CL-26	(2)1/2"	(2)1/2"	(1)1/2"	71.0	50
384D* Gangable	3-1/2	18.0	CL-26	(4)1/2"	(2)1/2"	(1)1/2"	82.0	25
384DLE Gangable	3-1/2	18.0	CL-26	(4)1/2"	(2)1/2"	(1)1/2"	79.0	25
384D-NL Gangable	3-1/2	18.0	CL-26	(4)1/2"	(2)1/2"	(1)1/2"	87.0	25
384D-VBPL Gangable	3-1/2	18.0	CL-26	(2)1/2"	(2)1/2"	(1)1/2"	86.0	25



384D-VBPL
3-1/2" Deep, Gangable
Plain vertical bracket
set back 3/4"

* Plaster ears support GFCI and decorative cover plates.