









3M™ Direct Connect Accessories

	2876	2892	8006
			
UPC #	054007-71921	054007-19483	054007-34027
Product Name	3M™ Large Clip Direct-Connect Transmitter Cable for Most Cable/Fault Locators 2876	3M™ Small Clip Direct-Connect Transmitter Cable for All Cable/Fault Locators 2892	3M™ Ground Rod 8006
Description	Two lead, 10 ft cables used for direct connection to cable and ground.	Two lead, 10 ft cables used for direct connection to cable and ground.	For applying ground capability. Stainless steel.
Compatible With	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573
Packaging	1 each per box	1 each per box	1 each per box
Minimum Order	1 each	1 each	1 each
	9012	9043	
			
UPC #	054007-31275	054007-34026	
Product Name	3M™ Direct Connect, 5-foot Transmitter Cable, Telephone 9012	3M™ Ground Extension Cable 9043	
Description	Two lead, 5 ft cables used for direct connection to conductor and ground. The 9012 cable has smaller Telco style alligator clips with an insulation piercing needle incorporated.	Extends ground capability to 12 ft.	
Compatible With	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573	
Packaging	1 each per box	1 each per box	
Minimum Order	1 each	1 each	

3M™ Couplers

	1196	1196/C	3001	3019
				
UPC #	054007-19042	051115-18603	054007-31258	054007-91427
Product Name	3M™ 6" Dyna-Coupler with Pouch, 1196	3M™ 6" Dyna-Coupler with Pouch & 9011 Coupler Cable, 1196/C	3M™ 3" Dyna-Coupler, 3001	3M™ Cable Locator Coupler Accessory Kit 3019
Description	Permits coupling of RF trace tone to large diameter cables, bundle cables, and cables enclosed in accessible non-metallic ducts. For use on cables and conduits with a maximum diameter of 6.9 feet.	Permits coupling of RF trace tone to large diameter cables, bundle cables, and cables enclosed in accessible non-metallic ducts. For use on cables and conduits with a maximum diameter of 6.9 feet.	Permits coupling of RF trace tone to cables with a maximum diameter of 3 feet.	The 3019 Accessory Kit contains a 3001 3 inch Dyna-coupler and a 9011 Coupler Cable with a case that can be attached onto the locator.
Compatible With	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573	2250/2273, 2220M, 2250M/2273M, 2550/2573
Packaging	1 each per box	1 each per box	1 each per box	1 each per box
Minimum Order	1 each	1 each	1 each	1 each