

3M(TM) SILICONE LUBRICANT

04/22/16

3M

SAFETY DATA SHEET

COPYRIGHT, 2016, 3M COMPANY.

ALL RIGHTS RESERVED. COPYING AND/OR DOWNLOADING OF THIS INFORMATION FOR THE PURPOSE OF PROPERLY UTILIZING 3M PRODUCTS IS ALLOWED PROVIDED THAT:

(1) THE INFORMATION IS COPIED IN FULL WITH NO CHANGES UNLESS PRIOR WRITTEN AGREEMENT IS OBTAINED FROM 3M, AND

(2) NEITHER THE COPY NOR THE ORIGINAL IS RESOLD OR OTHERWISE DISTRIBUTED WITH THE INTENTION OF EARNING A PROFIT THEREON.

DOCUMENT GROUP: 05-6937-6

VERSION NUMBER: 24.00

ISSUE DATE: 04/22/16

SUPERCEDES DATE: 04/28/15

SECTION 1: IDENTIFICATION

1.1. PRODUCT IDENTIFIER: 3M(TM) SILICONE LUBRICANT

PRODUCT IDENTIFICATION NUMBERS:

62-4678-0930-7, 62-4678-0931-5, 62-4678-4930-3, 62-4678-4935-2,
78-8033-2219-3

1.2. RECOMMENDED USE AND RESTRICTIONS ON USE:

RECOMMENDED USE: INDUSTRIAL USE

1.3. SUPPLIER'S DETAILS:

MANUFACTURER: 3M

DIVISION: INDUSTRIAL ADHESIVES AND TAPES DIVISION

ADDRESS:

3M CENTER

ST. PAUL, MN 55144-1000

USA

TELEPHONE: 1-888-3M HELPS (1-888-364-3577)

1.4. EMERGENCY TELEPHONE NUMBER:

1-800-364-3577 OR (651) 737-6501 (24 HOURS)

SECTION 2: HAZARD IDENTIFICATION

2.1. HAZARD CLASSIFICATION:

FLAMMABLE AEROSOL: CATEGORY 1.

GAS UNDER PRESSURE: LIQUEFIED GAS.

SERIOUS EYE DAMAGE/IRRITATION: CATEGORY 2B.

SIMPLE ASPHYXIANANT.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): CATEGORY 1.

SPECIFIC TARGET ORGAN TOXICITY (CENTRAL NERVOUS SYSTEM): CATEGORY 3.

2.2. LABEL ELEMENTS:

SIGNAL WORD: DANGER

SYMBOLS:

FLAME

GAS CYLINDER

EXCLAMATION MARK

HEALTH HAZARD

PICTOGRAMS:

FLAME

GAS CYLINDER

EXCLAMATION MARK

HEALTH HAZARD

HAZARD STATEMENTS:

EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

CAUSES DAMAGE TO ORGANS: CARDIOVASCULAR SYSTEM

PRECAUTIONARY STATEMENTS:

GENERAL: KEEP OUT OF REACH OF CHILDREN.

PREVENTION:

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY.

USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

WASH THOROUGHLY AFTER HANDLING.

RESPONSE:

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

IF EXPOSED: CALL A POISON CENTER OR DOCTOR/PHYSICIAN.

SPECIFIC TREATMENT (SEE NOTES TO PHYSICIAN ON THIS LABEL).

STORAGE:

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50C/122F. KEEP CONTAINER TIGHTLY CLOSED. STORE LOCKED UP IN A WELL-VENTILATED PLACE.

DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH APPLICABLE LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS.

NOTES TO PHYSICIAN:

EXPOSURE MAY INCREASE MYOCARDIAL IRRITABILITY. DO NOT ADMINISTER SYMPATHOMIMETIC DRUGS UNLESS ABSOLUTELY NECESSARY.

2.3. HAZARDS NOT OTHERWISE CLASSIFIED:

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENTS CAN BE HARMFUL OR FATAL. MAY CAUSE FROSTBITE.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	C.A.S. NO.	% BY WT
ISOBUTANE	75-28-5	70 - 80 TRADE SECRET *
HEPTANE	142-82-5	15 - 25 TRADE SECRET *
POLY(DIMETHYLSILOXANE)	63148-62-9	3 - 7 TRADE SECRET *

*THE SPECIFIC CHEMICAL IDENTITY AND/OR EXACT PERCENTAGE (CONCENTRATION) OF THIS COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

SECTION 4: FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES:

INHALATION: REMOVE PERSON TO FRESH AIR. GET MEDICAL ATTENTION.

SKIN CONTACT:

THAW FROSTED SKIN WITH LUKEWARM WATER. DO NOT RUB AFFECTED AREA. GET MEDICAL ATTENTION.

EYE CONTACT:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. REMOVE CONTACT LENSES IF

EASY TO DO. CONTINUE RINSING. GET MEDICAL ATTENTION.

IF SWALLOWED: RINSE MOUTH. IF YOU FEEL UNWELL, GET MEDICAL ATTENTION.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:
SEE SECTION 11.1. INFORMATION ON TOXICOLOGICAL EFFECTS.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT
REQUIRED:

EXPOSURE MAY INCREASE MYOCARDIAL IRRITABILITY. DO NOT ADMINISTER
SYMPATHOMIMETIC DRUGS UNLESS ABSOLUTELY NECESSARY.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. SUITABLE EXTINGUISHING MEDIA:

USE A FIRE FIGHTING AGENT SUITABLE FOR THE SURROUNDING FIRE.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SUBSTANCE	CONDITION
CARBON MONOXIDE	DURING COMBUSTION
CARBON DIOXIDE	DURING COMBUSTION

5.3. SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:

WATER MAY NOT EFFECTIVELY EXTINGUISH FIRE; HOWEVER, IT SHOULD BE USED TO
KEEP FIRE-EXPOSED CONTAINERS AND SURFACES COOL AND PREVENT EXPLOSIVE
RUPTURE.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
EVACUATE AREA. KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO
SMOKING. USE ONLY NON-SPARKING TOOLS. VENTILATE THE AREA WITH FRESH AIR.
FOR LARGE SPILL, OR SPILLS IN CONFINED SPACES, PROVIDE MECHANICAL
VENTILATION TO DISPERSE OR EXHAUST VAPORS, IN ACCORDANCE WITH GOOD
INDUSTRIAL HYGIENE PRACTICE.

WARNING!

A MOTOR COULD BE AN IGNITION SOURCE AND COULD CAUSE FLAMMABLE GASES
OR VAPORS IN THE SPILL AREA TO BURN OR EXPLODE. REFER TO OTHER SECTIONS
OF THIS SDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZARDS,
RESPIRATORY PROTECTION, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.

6.2. ENVIRONMENTAL PRECAUTIONS: AVOID RELEASE TO THE ENVIRONMENT.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:
IF POSSIBLE, SEAL LEAKING CONTAINER. PLACE LEAKING CONTAINERS IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF NECESSARY OUTDOORS ON AN IMPERMEABLE SURFACE UNTIL APPROPRIATE PACKAGING FOR THE LEAKING CONTAINER OR ITS CONTENTS IS AVAILABLE. COLLECT AS MUCH OF THE SPILLED MATERIAL AS POSSIBLE USING NON-SPARKING TOOLS. PLACE IN A METAL CONTAINER APPROVED FOR TRANSPORTATION BY APPROPRIATE AUTHORITIES. SEAL THE CONTAINER. DISPOSE OF COLLECTED MATERIAL AS SOON AS POSSIBLE.

SECTION 7: HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING:
KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING. DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH THOROUGHLY AFTER HANDLING. AVOID CONTACT WITH OXIDIZING AGENTS (EG. CHLORINE, CHROMIC ACID ETC.)

7.2. CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITIES:
STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50C/122F. STORE AWAY FROM HEAT. STORE AWAY FROM ACIDS. STORE AWAY FROM OXIDIZING AGENTS.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS:

OCCUPATIONAL EXPOSURE LIMITS:
IF A COMPONENT IS DISCLOSED IN SECTION 3 BUT DOES NOT APPEAR IN THE TABLE BELOW, AN OCCUPATIONAL EXPOSURE LIMIT IS NOT AVAILABLE FOR THE COMPONENT.

INGREDIENT	C.A.S. NO.	AGENCY	LIMIT TYPE	ADDITIONAL COMMENTS
HEPTANE	142-82-5	ACGIH	TWA: 400 PPM; STEL: 500 PPM	
HEPTANE	142-82-5	OSHA	TWA: 2000 MG/M3 (500 PPM)	
ISOBUTANE	75-28-5	ACGIH	STEL: 1000 PPM	
NATURAL GAS	75-28-5	ACGIH	LIMIT VALUE NOT ESTABLISHED	

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

AIHA: AMERICAN INDUSTRIAL HYGIENE ASSOCIATION

CMRG: CHEMICAL MANUFACTURER'S RECOMMENDED GUIDELINES

OSHA:
UNITED STATES DEPARTMENT OF LABOR - OCCUPATIONAL SAFETY AND HEALTH
ADMINISTRATION

TWA: TIME-WEIGHTED-AVERAGE

STEL: SHORT TERM EXPOSURE LIMIT

CEIL: CEILING

8.2. EXPOSURE CONTROLS:

8.2.1. ENGINEERING CONTROLS:

DO NOT REMAIN IN AREA WHERE AVAILABLE OXYGEN MAY BE REDUCED. USE GENERAL DILUTION VENTILATION AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE EXPOSURES TO BELOW RELEVANT EXPOSURE LIMITS AND/OR CONTROL DUST/FUME/GAS/MIST/VAPORS/SPRAY. IF VENTILATION IS NOT ADEQUATE, USE RESPIRATORY PROTECTION EQUIPMENT.

8.2.2. PERSONAL PROTECTIVE EQUIPMENT (PPE):

EYE/FACE PROTECTION:

SELECT AND USE EYE/FACE PROTECTION TO PREVENT CONTACT BASED ON THE RESULTS OF AN EXPOSURE ASSESSMENT. THE FOLLOWING EYE/FACE PROTECTION(S) ARE RECOMMENDED: INDIRECT VENTED GOGGLES

SKIN/HAND PROTECTION:

SELECT AND USE GLOVES AND/OR PROTECTIVE CLOTHING APPROVED TO RELEVANT LOCAL STANDARDS TO PREVENT SKIN CONTACT BASED ON THE RESULTS OF AN EXPOSURE ASSESSMENT. SELECTION SHOULD BE BASED ON USE FACTORS SUCH AS EXPOSURE LEVELS, CONCENTRATION OF THE SUBSTANCE OR MIXTURE, FREQUENCY AND DURATION, PHYSICAL CHALLENGES SUCH AS TEMPERATURE EXTREMES, AND OTHER USE CONDITIONS.

CONSULT WITH YOUR GLOVE AND/OR PROTECTIVE CLOTHING MANUFACTURER FOR SELECTION OF APPROPRIATE COMPATIBLE GLOVES/PROTECTIVE CLOTHING. GLOVES MADE FROM THE FOLLOWING MATERIAL(S) ARE RECOMMENDED: NITRILE RUBBER

RESPIRATORY PROTECTION:

AN EXPOSURE ASSESSMENT MAY BE NEEDED TO DECIDE IF A RESPIRATOR IS REQUIRED. IF A RESPIRATOR IS NEEDED, USE RESPIRATORS AS PART OF A FULL RESPIRATORY PROTECTION PROGRAM. BASED ON THE RESULTS OF THE EXPOSURE ASSESSMENT, SELECT FROM THE FOLLOWING RESPIRATOR TYPE(S) TO REDUCE INHALATION EXPOSURE:

HALF FACEPIECE OR FULL FACEPIECE SUPPLIED-AIR RESPIRATOR

FOR QUESTIONS ABOUT SUITABILITY FOR A SPECIFIC APPLICATION, CONSULT WITH YOUR RESPIRATOR MANUFACTURER.

THERMAL HAZARDS: WEAR COLD INSULATING GLOVES/FACE SHIELD/EYE PROTECTION.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

GENERAL PHYSICAL FORM: LIQUID

ODOR, COLOR, GRADE: IN AEROSOL, TRANSPARENT, VERY SLIGHT ODOR

ODOR THRESHOLD: NO DATA AVAILABLE

PH: NOT APPLICABLE

MELTING POINT: NO DATA AVAILABLE

BOILING POINT: NO DATA AVAILABLE

FLASH POINT:

-50 DEG. F [TEST METHOD: TAGLIABUE CLOSED CUP] [DETAILS: CONDITIONS:
PROPELLANT]

EVAPORATION RATE: 1.9 [REF STD: WATER=1]

FLAMMABILITY (SOLID, GAS): NOT APPLICABLE

FLAMMABLE LIMITS (LEL): APPROXIMATELY 1.5% VOLUME

FLAMMABLE LIMITS (UEL): APPROXIMATELY 8% VOLUME

VAPOR DENSITY: 2.97 [REF STD: AIR=1]

DENSITY: 0.64 G/ML

SPECIFIC GRAVITY: 0.640 [REF STD: WATER=1]

SOLUBILITY IN WATER: NIL

SOLUBILITY- NON-WATER: NO DATA AVAILABLE

PARTITION COEFFICIENT N-OCTANOL/WATER: NO DATA AVAILABLE

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

DECOMPOSITION TEMPERATURE: NO DATA AVAILABLE

VISCOSITY: NOT APPLICABLE

HAZARDOUS AIR POLLUTANTS: 0% WEIGHT [TEST METHOD: CALCULATED]

MOLECULAR WEIGHT: NO DATA AVAILABLE

VOLATILE ORGANIC COMPOUNDS:

<=606 G/L [TEST METHOD: CALCULATED SCAQMD RULE 443.1] [DETAILS: MATERIAL
VOC]

VOLATILE ORGANIC COMPOUNDS:

<=94.7% [TEST METHOD: CALCULATED PER CARB TITLE 2]

SOLIDS CONTENT: 0%

SECTION 10: STABILITY AND REACTIVITY

10.1. REACTIVITY:

THIS MATERIAL MAY BE REACTIVE WITH CERTAIN AGENTS UNDER CERTAIN CONDITIONS
- SEE THE REMAINING HEADINGS IN THIS SECTION.

10.2. CHEMICAL STABILITY: STABLE.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

10.4. CONDITIONS TO AVOID: HEAT

10.5. INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS

10.6. HAZARDOUS DECOMPOSITION PRODUCTS:

SUBSTANCE	CONDITION
-----------	-----------

NONE KNOWN.

REFER TO SECTION 5.2 FOR HAZARDOUS DECOMPOSITION PRODUCTS DURING
COMBUSTION.

SECTION 11: TOXICOLOGICAL INFORMATION

THE INFORMATION BELOW MAY NOT BE CONSISTENT WITH THE MATERIAL
CLASSIFICATION IN SECTION 2 IF SPECIFIC INGREDIENT CLASSIFICATIONS ARE
MANDATED BY A COMPETENT AUTHORITY. IN ADDITION, TOXICOLOGICAL DATA ON
INGREDIENTS MAY NOT BE REFLECTED IN THE MATERIAL CLASSIFICATION AND/OR THE
SIGNS AND SYMPTOMS OF EXPOSURE, BECAUSE AN INGREDIENT MAY BE PRESENT BELOW
THE THRESHOLD FOR LABELING, AN INGREDIENT MAY NOT BE AVAILABLE FOR
EXPOSURE, OR THE DATA MAY NOT BE RELEVANT TO THE MATERIAL AS A WHOLE.

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS:

SIGNS AND SYMPTOMS OF EXPOSURE:

BASED ON TEST DATA AND/OR INFORMATION ON THE COMPONENTS, THIS MATERIAL MAY
PRODUCE THE FOLLOWING HEALTH EFFECTS:

INHALATION:

INTENTIONAL CONCENTRATION AND INHALATION MAY BE HARMFUL OR FATAL.

SIMPLE ASPHYXIATION:

SIGNS/SYMPTOMS MAY INCLUDE INCREASED HEART RATE, RAPID RESPIRATIONS,
DROWSINESS, HEADACHE, INCOORDINATION, ALTERED JUDGMENT, NAUSEA, VOMITING,
LETHARGY, SEIZURES, COMA, AND MAY BE FATAL.

RESPIRATORY TRACT IRRITATION:

SIGNS/SYMPTOMS MAY INCLUDE COUGH, SNEEZING, NASAL DISCHARGE, HEADACHE,
HOARSENESS, AND NOSE AND THROAT PAIN.

MAY CAUSE ADDITIONAL HEALTH EFFECTS (SEE BELOW).

SKIN CONTACT:

FROSTBITE:

SIGNS/SYMPTOMS MAY INCLUDE INTENSE PAIN, DISCOLORATION OF SKIN, AND TISSUE DESTRUCTION.

MILD SKIN IRRITATION:

SIGNS/SYMPTOMS MAY INCLUDE LOCALIZED REDNESS, SWELLING, ITCHING, AND DRYNESS.

EYE CONTACT:

FROSTBITE:

SIGNS/SYMPTOMS MAY INCLUDE INTENSE PAIN, CLOUDING OF THE CORNEA, REDNESS, SWELLING, AND BLINDNESS.

MODERATE EYE IRRITATION:

SIGNS/SYMPTOMS MAY INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND BLURRED OR HAZY VISION.

INGESTION:

GASTROINTESTINAL IRRITATION:

SIGNS/SYMPTOMS MAY INCLUDE ABDOMINAL PAIN, STOMACH UPSET, NAUSEA, VOMITING AND DIARRHEA.

MAY CAUSE ADDITIONAL HEALTH EFFECTS (SEE BELOW).

ADDITIONAL HEALTH EFFECTS:

SINGLE EXPOSURE MAY CAUSE TARGET ORGAN EFFECTS:

CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION:

SIGNS/SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, NAUSEA, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS, AND UNCONSCIOUSNESS.

SINGLE EXPOSURE, ABOVE RECOMMENDED GUIDELINES, MAY CAUSE:

CARDIAC SENSITIZATION:

SIGNS/SYMPTOMS MAY INCLUDE IRREGULAR HEARTBEAT (ARRHYTHMIA), FAINTNESS, CHEST PAIN, AND MAY BE FATAL.

TOXICOLOGICAL DATA:

IF A COMPONENT IS DISCLOSED IN SECTION 3 BUT DOES NOT APPEAR IN A TABLE BELOW, EITHER NO DATA ARE AVAILABLE FOR THAT ENDPOINT OR THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION.

ACUTE TOXICITY:

NAME	ROUTE	SPECIES	VALUE
OVERALL PRODUCT	DERMAL		NO DATA AVAILABLE; CALCULATED ATE >5,000 MG/KG

OVERALL PRODUCT	INGESTION		NO DATA AVAILABLE; CALCULATED ATE >5,000 MG/KG
ISOBUTANE	INHALATION- GAS (4 HOURS)	RAT	LC50 276,000 PPM
HEPTANE	DERMAL	RABBIT	LD50 3,000 MG/KG
HEPTANE	INHALATION- VAPOR (4 HOURS)	RAT	LC50 103 MG/L
HEPTANE	INGESTION	RAT	LD50 >15,000 MG/KG
POLY (DIMETHYL- SILOXANE)	DERMAL	RABBIT	LD50 >19,400 MG/KG
POLY (DIMETHYL- SILOXANE)	INGESTION	RAT	LD50 >17,000 MG/KG

ATE = ACUTE TOXICITY ESTIMATE

SKIN CORROSION/IRRITATION:

NAME	SPECIES	VALUE
ISOBUTANE	PROFESSIONAL JUDGMENT	NO SIGNIFICANT IRRITATION
HEPTANE	HUMAN	MILD IRRITANT
POLY (DIMETHYLSILOXANE)	RABBIT	NO SIGNIFICANT IRRITATION

SERIOUS EYE DAMAGE/IRRITATION:

NAME	SPECIES	VALUE
ISOBUTANE	PROFESSIONAL JUDGMENT	NO SIGNIFICANT IRRITATION
HEPTANE	PROFESSIONAL JUDGMENT	MODERATE IRRITANT
POLY (DIMETHYLSILOXANE)	RABBIT	NO SIGNIFICANT IRRITATION

SKIN SENSITIZATION:

FOR THE COMPONENT/COMPONENTS, EITHER NO DATA ARE CURRENTLY AVAILABLE OR THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION.

RESPIRATORY SENSITIZATION:

FOR THE COMPONENT/COMPONENTS, EITHER NO DATA ARE CURRENTLY AVAILABLE OR THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION.

GERM CELL MUTAGENICITY:

NAME	ROUTE	VALUE
------	-------	-------

ISOBUTANE IN VITRO NOT MUTAGENIC

HEPTANE IN VITRO NOT MUTAGENIC

CARCINOGENICITY:

FOR THE COMPONENT/COMPONENTS, EITHER NO DATA ARE CURRENTLY AVAILABLE OR THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION.

REPRODUCTIVE TOXICITY:

REPRODUCTIVE AND/OR DEVELOPMENTAL EFFECTS:

FOR THE COMPONENT/COMPONENTS, EITHER NO DATA ARE CURRENTLY AVAILABLE OR THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION.

TARGET ORGAN(S) :

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE:

NAME	ROUTE	TARGET ORGAN(S)	VALUE
ISOBUTANE	INHALATION	CARDIAC SENSITIZATION	CAUSES DAMAGE TO ORGANS
ISOBUTANE	INHALATION	CENTRAL NERVOUS SYSTEM DEPRESSION	MAY CAUSE DROWSINESS OR DIZZINESS
ISOBUTANE	INHALATION	RESPIRATORY IRRITATION	ALL DATA ARE NEGATIVE
HEPTANE	INHALATION	CENTRAL NERVOUS SYSTEM DEPRESSION	MAY CAUSE DROWSINESS OR DIZZINESS
HEPTANE	INHALATION	RESPIRATORY IRRITATION	SOME POSITIVE DATA EXIST, BUT THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION
HEPTANE	INGESTION	CENTRAL NERVOUS SYSTEM DEPRESSION	MAY CAUSE DROWSINESS OR DIZZINESS

NAME	SPECIES	TEST RESULT	EXPOSURE DURATION
ISOBUTANE	MULTIPLE ANIMAL SPECIES	NOAEL NOT AVAILABLE	
ISOBUTANE	HUMAN AND ANIMAL	NOAEL NOT AVAILABLE	
ISOBUTANE	MOUSE	NOAEL NOT AVAILABLE	
HEPTANE	HUMAN	NOAEL NOT AVAILABLE	
HEPTANE	HUMAN	NOAEL NOT AVAILABLE	
HEPTANE	HUMAN	NOAEL NOT AVAILABLE	

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE:

NAME	ROUTE	TARGET ORGAN(S)	VALUE
------	-------	-----------------	-------

ISOBUTANE	INHALATION	KIDNEY AND/OR BLADDER	SOME POSITIVE DATA EXIST, BUT THE DATA ARE NOT SUFFICIENT FOR CLASSIFICATION
-----------	------------	--------------------------	--

HEPTANE	INHALATION	LIVER NERVOUS SYSTEM KIDNEY AND/OR BLADDER	ALL DATA ARE NEGATIVE
---------	------------	--	-----------------------

NAME	SPECIES	TEST RESULT	EXPOSURE DURATION
ISOBUTANE	RAT	NOAEL 4,500 PPM	13 WEEKS
HEPTANE	RAT	NOAEL 12 MG/L	26 WEEKS

ASPIRATION HAZARD:

NAME	VALUE
------	-------

HEPTANE	ASPIRATION HAZARD
---------	-------------------

PLEASE CONTACT THE ADDRESS OR PHONE NUMBER LISTED IN SECTION 1 OF THIS SDS FOR ADDITIONAL TOXICOLOGICAL INFORMATION ON THIS MATERIAL AND/OR ITS COMPONENTS.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

PLEASE CONTACT THE ADDRESS OR PHONE NUMBER LISTED IN SECTION 1 OF THIS SDS FOR ADDITIONAL ECOTOXICOLOGICAL INFORMATION ON THIS MATERIAL AND/OR ITS COMPONENTS.

CHEMICAL FATE INFORMATION:

PLEASE CONTACT THE ADDRESS OR PHONE NUMBER LISTED IN SECTION 1 OF THIS SDS FOR ADDITIONAL CHEMICAL FATE INFORMATION ON THIS MATERIAL AND/OR ITS COMPONENTS.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHODS:

DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH THE LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS.

INCINERATE IN A PERMITTED WASTE INCINERATION FACILITY. AS A DISPOSAL ALTERNATIVE, UTILIZE AN ACCEPTABLE PERMITTED WASTE DISPOSAL FACILITY. EMPTY DRUMS/BARRELS/CONTAINERS USED FOR TRANSPORTING AND HANDLING HAZARDOUS CHEMICALS (CHEMICAL SUBSTANCES/MIXTURES/PREPARATIONS CLASSIFIED AS HAZARDOUS AS PER APPLICABLE REGULATIONS) SHALL BE CONSIDERED, STORED, TREATED & DISPOSED OF AS HAZARDOUS WASTES UNLESS OTHERWISE DEFINED BY APPLICABLE WASTE REGULATIONS. CONSULT WITH THE RESPECTIVE REGULATING AUTHORITIES TO DETERMINE THE AVAILABLE TREATMENT AND DISPOSAL FACILITIES.

EPA HAZARDOUS WASTE NUMBER (RCRA): D001 (IGNITABLE)

SECTION 14: TRANSPORT INFORMATION

FOR TRANSPORT INFORMATION, PLEASE VISIT:
HTTP://3M.COM/TRANSPORTINFO OR CALL 1-800-364-3577 OR 651-737-6501.

SECTION 15: REGULATORY INFORMATION

15.1. US FEDERAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES

REACTIVITY HAZARD: NO

PRESSURE HAZARD: YES

IMMEDIATE HAZARD: YES

DELAYED HAZARD: NO

15.2. STATE REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

15.3. CHEMICAL INVENTORIES:

THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE CHEMICAL NOTIFICATION REQUIREMENTS OF TSCA.

CONTACT 3M FOR MORE INFORMATION.

15.4. INTERNATIONAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

THIS SDS HAS BEEN PREPARED TO MEET THE U.S. OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA HAZARD CLASSIFICATION:

HEALTH 2

FLAMMABILITY 4

INSTABILITY 0

SPECIAL HAZARDS NONE

AEROSOL STORAGE CODE: 3

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD RATINGS ARE DESIGNED FOR USE BY EMERGENCY RESPONSE PERSONNEL TO ADDRESS THE HAZARDS THAT ARE PRESENTED BY SHORT-TERM, ACUTE EXPOSURE TO A MATERIAL UNDER CONDITIONS OF FIRE, SPILL, OR SIMILAR EMERGENCIES. HAZARD RATINGS ARE PRIMARILY BASED ON THE INHERENT PHYSICAL AND TOXIC PROPERTIES OF THE MATERIAL BUT ALSO INCLUDE THE TOXIC PROPERTIES OF COMBUSTION OR DECOMPOSITION PRODUCTS THAT ARE KNOWN TO BE GENERATED IN SIGNIFICANT QUANTITIES.

DOCUMENT GROUP: 05-6937-6

VERSION NUMBER: 24.00

ISSUE DATE: 04/22/16

SUPERCEDES DATE: 04/28/15

DISCLAIMER:

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. USER IS RESPONSIBLE FOR DETERMINING WHETHER THE 3M PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A 3M PRODUCT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE AND CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE 3M PRODUCT TO DETERMINE WHETHER IT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION.

3M PROVIDES INFORMATION IN ELECTRONIC FORM AS A SERVICE TO ITS CUSTOMERS. DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, 3M MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ACCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABASE MAY NOT BE AS CURRENT AS THE INFORMATION IN THE SDS AVAILABLE DIRECTLY FROM 3M

3M USA SDSS ARE AVAILABLE AT WWW.3M.COM