

3M™ Spray Wire Pulling Lubricant

3M™ Spray Wire Pulling Lubricant is a clean, non-staining, high-performance, thin liquid cable pulling lubricant. 3M™ Spray Lubricant is easily applied by either spraying or wiping. The lubricant has excellent cling and wetting properties for all cable types. The slightly gelled character of the lubricant helps to coat and wet the cable for difficult or complex cable pulls.

Applications Lubricant

Lubricant Type Spray




RoHS 2011/65/EU Yes

Agency Approval



Country of Origin



	WLS-QT	WLS-1	WLS-5
			
UPC	051128-57925	051128-57926	051128-57927
Size	1 quart bottle	1 gallon pail	5 gallon pail
Temperature Use Range	20–120°F (-5–49°C)	20–120°F (-5–49°C)	20–120°F (-5–49°C)
Color	Clear	Clear	Clear
Case Qty.	12	4	1

3M™ Wire Pulling Lubricant Gel

3M™ Clear Wire Pulling Lubricant is a clear, colorless, slow-drying, easy-to-apply gel which is an excellent lubricant for everyday pulling of both electrical and communication cable. The clear formula makes this an ideal choice where cleanliness is a concern. 3M™ Clear Wire Pulling Lubricant has a low residue, less than 5% solids.

Applications Lubricant

Lubricant Type Gel

RoHS 2011/65/EU Yes

Agency Approval



Country of Origin



Order No.	UPC	Size	Weight	Temperature Use Range	Color	Case Qty.
WL-QT	054007-50622	1 quart bottle	28.0 lbs. (12,7 kg)	20–120°F (-5–49°C)	Clear	12
WL-1	054007-50623	1 gallon pail	35.0 lbs. (15,9 kg)	20–120°F (-5–49°C)	Clear	4
WL-5	054007-50624	5 gallon pail	42.0 lbs. (19,05 kg)	20–120°F (-5–49°C)	Clear	1