



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Main

Range	TeSys
Product name	TeSys LC1D.K
Product or component type	Capacitor duty contactor
Device short name	LC1D.K
Device application	Control
Contact application	Power factor correction
Utilisation category	AC-6b
Poles description	3P
Power pole contact composition	3 NO
Device location in system	Line interruption Inside delta interruption
[Ue] rated operational voltage	Power circuit 690 V AC 50/60 Hz
Reactive power rating	35 Kvar 230 V AC 50 Hz 140 °F (60 °C) 63 Kvar 400 V AC 50 Hz 140 °F (60 °C) 67 Kvar 440 V AC 50 Hz 140 °F (60 °C) 104 Kvar 690 V AC 50 Hz 140 °F (60 °C) 30 Kvar 230 V AC 60 Hz 140 °F (60 °C) 60 Kvar 460 V AC 60 Hz 140 °F (60 °C) 80 kvar 575 V AC 60 Hz 140 °F (60 °C)
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	400 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 2 NC instantaneous
Electrical durability	300000 Cycles 400 V 200000 cycles 690 V
Mounting support	DIN rail Plate
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	IECEE CB Scheme UL CSA
Connections - terminals	Control circuit screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid Control circuit screw clamp terminals 2 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid Control circuit screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Control circuit screw clamp terminals 2 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Control circuit screw clamp terminals 1 0.00... 0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible with cable end Control circuit screw clamp terminals 2 0.00... 0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) solid Power circuit connector 2 0.01...0.04 in <sup>2</sup> (4... 25 mm <sup>2</sup> ) solid Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) flexible without cable end Power circuit connector 2 0.01...0.04 in <sup>2</sup> (4... 25 mm <sup>2</sup> ) flexible without cable end Power circuit connector 1 0.01...0.08 in <sup>2</sup> (4... 50 mm <sup>2</sup> ) flexible with cable end Power circuit connector 2 0.01...0.02 in <sup>2</sup> (4... 16 mm <sup>2</sup> ) flexible with cable end
Tightening torque	Power circuit 79.66 lbf.in (9 N.m) connector Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals
Maximum operating rate	240 cyc/h

## Complementary

Auxiliary contacts type	Mechanically linked 1 NO + 2 NC IEC 60947-5-1
-------------------------	---

## Environment

IP degree of protection	IP20 front face IEC 60529
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Maximum Height	7.09 in (180 mm)
Maximum Width	3.35 in (85 mm)
Maximum Depth	6.06 in (154 mm)
Net Weight	3.64 lb(US) (1.65 kg)

## Ordering and shipping details

Category	22359 - CTR, TESYS D, OPEN, 80-150A AC&DC
Discount Schedule	I12
GTIN	03389110060720
Nbr. of units in pkg.	1
Package weight(Lbs)	3.98 lb(US) (1.81 kg)
Returnability	No
Country of origin	CZ

## Packing Units

Package 1 Height	1.900 dm
Package 1 width	1.350 dm
Package 1 Length	1.700 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------