

600-I HAND HELD POWER DRIVE

Introducing the lightest
and easiest to handle
Power Drive from RIDGID®



BENEFITS

- Lightweight and easy to handle for service and repair
- Over molded handle and contoured grip provide optimal control
- Screw in brush covers reduces service time
- Durable die cast gear housing and fiberglass reinforced plastic body to withstand demanding job site conditions
- Dual "V" Jaw Reaction Arm firmly prevents slipping

SPECIFICATIONS

- Capacity: 1/8" – 1/4" (3 mm - 32 mm) (11R Die Head)
- Weight: 12.7 lbs. (5.8 kg), Power Drive Only
- Size: 20 in. (508 mm) L x 3.75 in. (95mm) W x 7.5 in. (191mm) H
- Motor Type: Universal Single Phase
- Motor Wattage: 1020W (230V), 1270W (115V)
- Available Voltages/Phases: 115V/1 Ph, 230V/1Ph, 220V/1 Ph
- Amps: 12A (115V), 5A (230V, 220V)
- Operating Speed (No Load): 32 RPM (115V), 36 RPM (230V)
- Controls: FORWARD/REVERSE Slide Switch, ON/OFF Two-Step Momentary Contact
- Gear Head: Die Cast Aluminum Permanently Greased
- Body & Handle: Durable Heavy-Duty Fiberglass Reinforced Plastic

ORDERING INFORMATION

| CATALOG NO. | DESCRIPTION | WEIGHT | |
|-------------|--|--------|------|
| | | (lb.) | (kg) |
| 44913 | 600-I 115V w/o Die Heads w/Case Only and Support Arm | 29.1 | 13.2 |
| 44918 | 600-I 115V 1/2" – 1/4" NPT w/Case Support Arm | 41.0 | 18.6 |
| 45923 | 602 Support Arm | 4.0 | 1.8 |
| 46668 | Carrying Case | 12.0 | 5.5 |
| 10883 | 418 Oiler With 1 Gallon NuClear Oil | 17.0 | 7.7 |
| 16703 | 425 1/8" – 2 1/2" Portable TRISTAND Vise | 32.0 | 14.5 |
| 36273 | 460-6 1/8" – 6" Portable TRISTAND Vise | 47.0 | 21.0 |






RIDGID.COM



Standard Equipment

- 600-I Hand-Held Power Drive
- 602 Support Arm
- Carrying Case
- 1/2", 3/4", 1" & 1 1/4" 11R Die Heads

Comparison of RIDGID Power Drive Features

| |  RIDGID 700 PD |  RIDGID 690-I PD |  RIDGID 600-I PD |
|-----------------------------|---|--|---|
| Pipe Capacity | 1/8" - 2" | 1/8" - 2" | 1/8" - 1 1/4" |
| Bolt Capacity | 1/4" - 1" | N/A | N/A |
| Drive 258/258XL Pipe Cutter | YES | NO | NO |
| Weight (PD Only) | 25 lbs. | 21 lbs. | 13 lbs. |
| Length | 28 1/4 Inch | 24 Inch | 20 Inch |
| Body and Handle | Cast Aluminum | Cast Aluminum & Heavy-Duty Fiberglass Reinforced Plastic | Cast Aluminum & Heavy-Duty Fiberglass Reinforced Plastic |
| Spindle Speed (No Load) | 32 RPM | 32 RPM | 32 RPM |
| Die Heads | 12-R | 11-R | 11-R |
| Dies | 12-R | 12-R | 12-R |
| Usage/Applications | Heavy-Duty/Mech/Elect Contractor | Service/Repair Plumber/ Maintenance (2") | Service/Repair Plumber/ Maintenance (1 1/4") |
| Certifications/Approvals | | UL/CSA/RoHS/WEEE | |