VH224N

Heavy Duty Safety Switch Fused Viewing Window Type 1 240V 200A 2 POLE neutral



Main Produ

Product Single Throw Safety Switch Duty Rating Heavy duty Device Application Heavy application Disconnect Type Fusible disconnect Factory Installed Neutral Neutral (factory installed) Number of Poles 2 Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors 40 hp at 250 V DC		
Device Application Heavy application Disconnect Type Fusible disconnect Factory Installed Neutral Neutral (factory installed) Number of Poles 2 Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Product	Single Throw Safety Switch
Disconnect Type Fusible disconnect Factory Installed Neutral Neutral (factory installed) Number of Poles 2 Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Duty Rating	Heavy duty
Factory Installed Neutral Neutral (factory installed) Number of Poles 2 Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Device Application	Heavy application
Number of Poles 2 Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Disconnect Type	Fusible disconnect
Current Rating 200 A Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Factory Installed Neutral	Neutral (factory installed)
Voltage Rating 250 V DC 240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Number of Poles	2
240 V AC Enclosure Rating NEMA 1 steel Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Current Rating	200 A
Motor power hp 15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Voltage Rating	
25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors	Enclosure Rating	NEMA 1 steel
	Motor power hp	25 Hp at 240 V AC 50-60 Hz for 3 phase motors

Complementary

Short-circuit current	10 KA for H, K, J or R without fuse rejection clips 200 KA for R with fuse rejection clips 200 kA for J
Fuse type	H or K R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire (2P + N)
Wire Size	AWG 6250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)
Depth	8.6 in (218.44 mm)
Width	16.61 in (421.89 mm)
Height	28.93 in (734.82 mm)
Net Weight	53.51 lb(US) (24.27 kg)
Services	Field installed kit available
Condition of use	For USA For Mexico

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00008-H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	3606485893266
Returnability	No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	19.38 in (49.2125 cm)	
Package 1 Width	8.31 in (21.1137 cm)	
Package 1 Length	30.00 in (76.2 cm)	
Package 1 Weight	54.45 lb(US) (24.7 kg)	