

Product data sheet

Characteristics

140DAI35300

discrete input module Modicon Quantum - 32 I - 24 V AC

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1850.00 USD



Main

Commercial Status	Commercialised
Range of product	Modicon Quantum automation platform
Product or component type	VAC discrete input modules
Software name	Concept ProWORX 32 Unity Pro
Discrete input number	32

Complementary

Group of channels	4
Addressing requirement	2 input words
Discrete input voltage	24 V AC
Input current	<= 13.2 mA 47...53 Hz <= 11.1 mA 57...63 Hz
Voltage state1 guaranteed	14...30 V AC at 47...53 Hz 12...30 V AC at 57...63 Hz
Voltage state 0 guaranteed	0...5 V at 47...53 Hz 0...5 V at 57...63 Hz
Input impedance	3100 Ohm capacitive at 47...53 Hz 2600 Ohm capacitive at 57...63 Hz
Network frequency limits	47...63 Hz
Leakage current	<= 1.9 mA
Absolute maximum input	50 V 1 cycle 32 V 10 s 30 V continuous
Response time	7.3...12.3 ms On-Off 4.9...0.75 ms x line cycle Off-On
Isolation between group	1780 Vrms for 1 minute
Isolation between group and bus	1780 Vrms for 1 minute
Bus current requirement	250 mA
Power dissipation in W	<= 10.9 W
Local signalling	32 LEDs green input status 1 LED red external fault detected (F) 1 LED green bus communication is present (Active)
Marking	CE
Module format	Standard
Product weight	0.75 lb(US) (0.34 kg)

Environment

Standards	CSA C22.2 No 142 UL 508
Product certifications	CUL FM Class 1 Division 2
Resistance to electrostatic discharge	8 kV on air conforming to IEC 801-2 4 kV contact conforming to IEC 801-2
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)

Ordering and shipping details

Category	18155 - QUANTUM I/O & POWER SUPPLIES
Discount Schedule	PC21
GTIN	00785901013945
Nbr. of units in pkg.	1
Package weight(Lbs)	1.01
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	CN

Contractual warranty

Period	18 months
--------	-----------