

ETP Steel Liquidtight Fittings


Type 4QS

45° and 90°


Use:

4QS liquidtight connectors and liquidtight flexible metallic conduit are used in applications where conditions of installation, operation or maintenance require flexibility or protection from liquids, vapors or solids such as: machine tool building, motor and transformer terminations, robotics assembly, air conditioning equipment installation and Class I, Division 2 wiring


Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches		
			A	B	C
3/8 (1/2 KO)	4QS-438	4QS-438T	1 1/4	5/8	1 3/32
1/2	4QS-450	4QS-450T	1 3/8	5/8	1 3/16
5/8	4QS-475	4QS-475T	1 1/2	5/8	1 7/16
1	4QS-4100	4QS-4100T	1 13/16	21/32	1 3/4
1 1/4	4QS-4125	4QS-4125T	2	11/16	2 5/32
1 1/2	4QS-4150	4QS-4150T	2 5/16	23/32	2 3/8
2	4QS-4200	4QS-4200T	2 9/16	23/32	2 7/8




Type 4QS-438—
Type 4QS-4200



Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches			
			A	B	C	D
3/8 (1/2 KO)	4QS-938	4QS-938T	1 19/32	5/8	1 3/32	5/8
1/2	4QS-950	4QS-950T	1 21/32	5/8	1 3/16	5/8
5/8	4QS-975	4QS-975T	1 25/32	5/8	1 7/16	29/32
1	4QS-9100	4QS-9100T	2 3/16	21/32	1 3/4	13/16
1 1/4	4QS-9125	4QS-9125T	2 3/8	11/16	2 5/32	1 1/4
1 1/2	4QS-9150	4QS-9150T	2 5/8	23/32	2 3/8	13/8
2	4QS-9200	4QS-9200T	3 1/16	23/32	2 7/8	1 11/16



Type 4QS-938—
Type 4QS-9200



Material/Finish:

Body: Malleable Iron /Zinc Plated

Gland, nut, ferrule and locknut:

Steel /Zinc Plated

Third Party Certification:



UL Listed: 11853



CSA Certified: 009795

UL Listed liquidtight flexible metal conduit fittings from 3/8" through 1 1/4" trade sizes are suitable for grounding under NEC 250.118(7).

Applicable Third Party Standards:

UL Standard: 514B

CSA Standard: C22.2 No. 18

NEMA: FB-1

Federal Spec: W-F-406E