

# CA3SK11BD

TeSys SK control relay - 1 NO + 1 NC - ≤ 690 V  
- 24 V DC standard coil

Product availability: Stock - Normally stocked in distribution facility

Price\*: 51.00 USD



## Main

Commercial Status	Commercialised
Range of product	TeSys SK control relay
Product or component type	Control relay
Device short name	CA3SK
Contacteur application	Control circuit
Utilisation category	AC-15 DC-13
Pole contact composition	1 NO + 1 NC
[Ue] rated operational voltage	≤ 690 V ≤ 400 Hz
Control circuit type	DC standard
Control circuit voltage	24 V DC

## Complementary

[Ith] conventional free air thermal current	10 A at ≤ 131 °F (55 °C)
Associated fuse rating	10 A gL conforming to IEC 60947 10 A gL conforming to VDE 0660
[Ui] rated insulation voltage	690 V conforming to CSA C22.2 No 14 690 V conforming to UL 508 690 V conforming to BS 5424 690 V conforming to VDE 0110 group C 690 V conforming to IEC 60947
Mounting support	Plate Rail
Connections - terminals	Screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (0.35...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 0...0 in <sup>2</sup> (0.35...1.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (0.35...6 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (0.5...6 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 0...0.01 in <sup>2</sup> (1.5...4 mm <sup>2</sup> ) - cable stiffness: solid Screw clamp terminals 1 cable(s) 0...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> ) - cable stiffness: solid
Tightening torque	7.08 lbf.in (0.8 N.m) - on screw clamp terminals pozidriv No 1
Control circuit voltage limits	0.1...0.75 U <sub>c</sub> at 122 °F (50 °C) drop-out 0.85...1.1 U <sub>c</sub> at 122 °F (50 °C) operational
Operating time	10...18 ms coil energisation and NC opening 6...8 ms coil de-energisation and NC closing 8...12 ms coil energisation and NO closing 4...6 ms coil de-energisation and NO opening
Mechanical durability	10 Mcycles
Operating rate	1200 cyc/h
Inrush power in W	2.2 W at 68 °F (20 °C)
Hold-in power consumption in W	2.2 W at 68 °F (20 °C)
Heat dissipation	2.2 W
Height	2.2 in (56 mm)
Width	1.06 in (27 mm)

Depth	2.19 in (55.5 mm)
Product weight	0.29 lb(US) (0.132 kg)

## Environment

Standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Ambient air temperature for storage	-58...158 °F (-50...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating in temperature

## Ordering and shipping details

Category	22371 - RELAYS, CONTROL
Discount Schedule	I12
GTIN	00785901866749
Nbr. of units in pkg.	1
Package weight(Lbs)	0.28
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	CZ

## Contractual warranty

Period	18 months
--------	-----------