

# HDL26050

## Molded Case Circuit Breaker

Product availability: Stock - Normally stocked in distribution facility

Price\*: 870.00 USD

### Main

|   |  |
|---|--|
| Commercial Status                                   | Commercialised   |
| Product or component type                           | Molded Case Circuit Breaker  |
| Range of product                                    | PowerPact H  |
| [In] rated current                                  | 50 A   |
| Poles description                                   | 2P   |
| Breaking capacity                                   | 20 kA 250 V DC<br>14 kA 600 V AC<br>18 kA 480 V AC<br>25 kA 240 V AC |
| [Ue] rated operational voltage                      | 250 V DC<br>600 V AC   |
| [Ics] rated service short-circuit breaking capacity | 80 %   |
| Trip unit technology                                | Thermal-magnetic   |
| Product certifications                              | CSA<br>IEC<br>UL listed  |
| Mounting mode                                       | Unit mount   |
| Breaking capacity code                              | D  |
| Electrical connection                               | Lugs line<br>Lugs load   |
| AWG gauge   | 14...3/0 AWG aluminium/copper  |
| Magnetic hold current                               | 400 A  |
| Magnetic tripping current                           | 850 A  |

### Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 01110 - HD,JD UNIT MT BREAKER/SWITCH              |
| Discount Schedule     | DE2   |
| GTIN                  | 00785901461890                                    |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 3.04  |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | US  |

### Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|