

LA1SK02

TeSys SK - auxiliary contact block - 2 NC

Product availability: Stock - Normally stocked in distribution facility

Price*: 16.90 USD



Main

Commercial Status	Commercialised
Range of product	TeSys SK TeSys SK control relay
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	2 NC
Connections - terminals	Screw clamp terminals 2 cable 0...0 in ² (0.35...1.5 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0...0.01 in ² (0.35...6 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0...0 in ² (0.35...2.5 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0.01 in ² (0.5...6 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0...0.01 in ² (1.5...4 mm ²) - cable stiffness: solid Screw clamp terminals 1 cable 0...0.01 in ² (1.5...6 mm ²) - cable stiffness: solid

Complementary

Mounting location	Front side
[Ui] rated insulation voltage	690 V - conforming to CSA C22.2 No 14 690 V - conforming to VDE 0110 group C 690 V - conforming to BS 5424 690 V - conforming to IEC 60947
[Ue] rated operational voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at <= 131 °F (55 °C)
Associated fuse rating	VDE 0660 IEC 60947
Tightening torque	7.08 lbf.in (0.8 N.m) - on screw clamp terminals
Width	1.06 in (27 mm)
Product weight	0.05 lb(US) (0.022 kg)

Environment

Standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Ambient air temperature for storage	-58...158 °F (-50...70 °C)
Operating altitude	6561.68 ft (2000 m) without derating in temperature

Ordering and shipping details

Category	22371 - RELAYS, CONTROL
Discount Schedule	I12
GTIN	00785901866763
Nbr. of units in pkg.	1
Package weight(Lbs)	0.06
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0718 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------