

NSYCVF300M24DPF

ClimaSys forced vent. IP54, 300m³/h, 24V DC, with outlet grille and filter G2



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 776.89 USD



Main

Commercial Status	Commercialised
Range of product	ClimaSys CV
Product or component type	Fan
Type of ventilation filter	Standard
Air flow	Free flow rate with standard filter: 69214.32 Gal/hr(US) (262 m ³ /h) at 50 Hz
[Us] rated supply voltage	12...30 V
Input voltage	24 V DC 50/60 Hz

Complementary

Rated power in W	13 W 50 Hz
[In] rated current	0.53 A 50 Hz
Noise level	55...56 dB
Bearing type	Ball
Height	External: 10.55 in (268 mm)
Width	External: 9.76 in (248 mm)
Depth	External: 4.07 in (103.4 mm)
Cut-out dimensions	223 x 223 mm
Product weight	2.43 lb(US) (1.1 kg)
Material	Injected thermoplastic (ASA PC) for outlet grille
Colour	Outlet grille: grey RAL 7035
Ambient air temperature for operation	14...158 °F (-10...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Maximum pressure	158 Pa flow rate 0 m ³ /h
Electrical connection	Faston connector
IP degree of protection	IP54
Device composition	1 power cord 1 cut-out template 1 outlet grille front 1 filter front of axial motor 2 protective grille on the front and rear surfaces 1 axial motor
Condition of use	Outside temperature must be 5 °C lower than inside temperature Filter must be cleaned and replaced regularly Surrounding environment must be relatively clean Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Ordering and shipping details

Category	80036 - ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	00785901869450
Nbr. of units in pkg.	1
Package weight(Lbs)	3.47
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------