

# Product data sheet

## Characteristics

# RSL1AB4BD

slim interface plug-in relay - Zelio RSL - 1 C/O  
standard - 24 V DC - 6 A

Product availability: Stock - Normally stocked in distribution facility

Price\*: 7.70 USD



### Main

Commercial Status	Commercialised
Range of product	Zelio Relay
Series name	Slim interface relay
Product or component type	Plug-in relay
Device short name	RSL
Contacts type and composition	1 C/O
Contacts operation	Standard
Control circuit voltage	24 V DC
[the] conventional enclosed thermal current	6 A at -40...131 °F (-40...55 °C)
Status LED	Without
Control type	Without push-button

### Complementary

Shape of pin	Flat (PCB type)
Average resistance	3390 Ohm at 23 °C +/- 10 %
Rated operational voltage limits	18...33.6 V DC
[Ui] rated insulation voltage	277 V conforming to cUL 250 V conforming to EN/IEC
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC
Contacts material	Silver alloy (AgSnO2)
[Ie] rated operational current	6 A (AC-1/DC-1) conforming to IEC/UL
Minimum switching current	100 mA
Maximum switching voltage	277 V
Minimum switching voltage	12 V
Maximum switching capacity	50 W 1500 VA
Minimum switching capacity	120 mW
Operating rate	<= 18000 cycles/hour no-load <= 360 cycles/hour under load
Mechanical durability	10000000 cycles
Electrical durability	60000 cycles (6 A at 250 V, AC-1) C/O
Operating time	12 ms reset 5 ms
Protection category	RT III
Operating position	Any position
Width	0.2 in (5 mm)
Height	1.1 in (28 mm)
Depth	0.73 in (18.5 mm)
Terminals description ISO n°1	(11-12-14)OC (A1-A2)CO
Product weight	0.01 lb(US) (0.0054 kg)
Load current	6 A at 250 V AC for 0.5 mm mounting distance

Average consumption in W	0.16 W
Drop-out voltage threshold	>= 0.05 U <sub>c</sub>

## Environment

Dielectric strength	4000 V AC (between coil and contact) 1000 V AC (between contacts)
Standards	EN/IEC 61810-1 UL 508 CSA C22.2 No 14
Product certifications	CSA UL EAC
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	+/- 1 mm (f = 10...55 Hz) conforming to EN/IEC 60068-2-6
IP degree of protection	IP40 conforming to EN/IEC 60529
Shock resistance	5 gn for 11 ms not operating conforming to EN/IEC 60068-2-27 10 gn for 11 ms in operation conforming to EN/IEC 60068-2-27
Ambient air temperature for operation	-40...131 °F (-40...55 °C)

## Ordering and shipping details

Category	21127 - ZELIO ICE CUBE RELAYS
Discount Schedule	CP2
GTIN	00785901695226
Nbr. of units in pkg.	10
Package weight(Lbs)	0.01
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	CZ

## Contractual warranty

Period	18 months
--------	-----------