Product data sheet Characteristics

VW3A3616

Ethernet TCP/IP communication card

Product availability: Stock - Normally stocked in distribution facility

Price*: 250.00 USD



Main

| Commercial Status | Commercialised | |
|------------------------------|--------------------|--|
| Product or component type | Communication card | |

Complementary

| Range compatibility | Altivar 32 Lexium 32 | |
|-----------------------------|---|--|
| Communication port protocol | Ethernet/IP Modbus TCP | |
| Electrical connection | 1 connector RJ45 Modbus TCP 1 connector RJ45 Ethernet/IP | |
| Transmission rate | 10/100 Mbps | |
| Addressing | IP addressing manual, BOOTP or DHCP | |
| Exchange mode | Half duplex and full duplex | |
| Communication service | Fixed communication monitoring adjusted by Ethernet IP scanner adaptor (Master) for Ethernet IP Master/Slave hierarchy ODVA AC drive profile and CiA 402 profile for Ethernet IP SNMP agent for Ethernet IP Communication monitoring for Modbus TCP I/O scanner : read/write, 6 words maximum for Modbus TCP Diagnostics (08) for Modbus TCP Read device identification (43) for Modbus TCP Read/Write multiple registers (23) for Modbus TCP Write multiple registers (16), 63 words max for Modbus TCP Write single register (06) for Modbus TCP Read input registers (04), 63 words max for Modbus TCP Read holding registers (03), 63 words max for Modbus TCP FDR Agent for Ethernet IP/Modbus TCP Up to 8 connections (includes connections of Modbus TCP/Ethernet IP) for Ethernet IP/Modbus TCP | |
| Web server | Embedded HTTP server | |
| Web services | Drive monitor Drive parameters Ethernet/IP scanner setup Ethernet/IP setup Ethernet statistics Message statistics Security | |
| Display type | 1 LED for Modbus TCP port activity 1 LED for Ethernet port activity 1 LED for NS (Network Status) 1 LED for MS (Module Status) | |
| Product weight | 0.66 lb(US) (0.3 kg) | |

Ordering and shipping details

| Category | 18297 - LEXIUM 32 DRIVES ACCESSORIES | |
|-----------------------|---|--|
| Discount Schedule | PC51 | |
| GTIN | 00785901924975 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 0.13 | |
| Product availability | Stock - Normally stocked in distribution facility | |
| Returnability | Υ | |
| Country of origin | SE | |

Offer Sustainability

| Sustainable offer status | Not Green Premium product |
|--------------------------|---|
| RoHS | Compliant - since 0936 - Schneider Electric declaration of conformity |

Contractual warranty

| | | , |
|------------------|--------|-----------|
| Period 18 months | Period | 18 months |