

XPSECPE5131P

module XPSEC - increasing the number of safety contacts - 24 V AC DC

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 500.00 USD



Main

Commercial Status	Commercialised
Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSECPE
Safety module application	Increasing the number of safety contacts
Function of module	Increasing the number of safety contacts
Safety level	Can reach SILCL 3 conforming to EN/IEC 62061 can reach the maximum safety level of module base Can reach PL e/category 4 conforming to EN/ISO 13849-1 can reach the maximum safety level of module base
Safety reliability data	PFHd = 2.47E-8 1/h conforming to EN/IEC 62061 DC = 0...99 % conforming to EN/ISO 13849-1 MTTFd > 100 years conforming to EN/ISO 13849-1
Output type	Relay 8 NO, volt-free
[Us] rated supply voltage	24 V DC (- 15...10 %) 24 V AC (- 15...10 %)
Number of additional circuits	2 NC + 1 solid state output

Complementary

Supply frequency	50/60 Hz
Power consumption	<= 4 VA
Input protection type	Internal, electronic
Breaking capacity	B300: inrush 3600 VA AC-15 for relay output B300: holding 360 VA AC-15 for relay output
Breaking capacity	20 mA/24 V for solid state output circuit 3 A/24 V - L/R = 50 ms, DC-13 for relay output
Output thermal current	6 A per relay for relay output
[Ith] conventional free air thermal current	< 24 A for relay output
Associated fuse rating	6 A gG for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum output current	10 mA for relay output
Minimum output voltage	5 V for relay output
Response time on input open	<= 10 ms
[Ui] rated insulation voltage	300 V, degree of pollution 2 conforming to EN/IEC 60947-5-1, DIN VDE 0110 parts 1 & 2
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III, conforming to EN/IEC 60947-5-1, DIN VDE 0110 parts 1 & 2
Local signalling	3 LEDs

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Connections - terminals	<p>Captive screw clamp terminals, clamping capacity: 2 x 0.5...2 x 1.5 mm² flexible cable with cable end, with double bezel</p> <p>Captive screw clamp terminals, clamping capacity: 2 x 0.25...2 x 1 mm² flexible cable with cable end, without bezel</p> <p>Captive screw clamp terminals, clamping capacity: 2 x 0.2...2 x 1 mm² flexible cable without cable end</p> <p>Captive screw clamp terminals, clamping capacity: 2 x 0.2...2 x 1 mm² solid cable without cable end</p> <p>Captive screw clamp terminals, clamping capacity: 1 x 0.25...1 x 1.5 mm² flexible cable with cable end, with bezel</p> <p>Captive screw clamp terminals, clamping capacity: 1 x 0.25...1 x 2.5 mm² flexible cable with cable end, without bezel</p> <p>Captive screw clamp terminals, clamping capacity: 1 x 0.2...1 x 2.5 mm² flexible cable without cable end</p> <p>Captive screw clamp terminals, clamping capacity: 1 x 0.2...1 x 2.5 mm² solid cable without cable end</p>
Mounting support	35 mm symmetrical DIN rail
Product weight	1.21 lb(US) (0.55 kg)

Environment

Standards	<p>EN/IEC 60204-1</p> <p>EN/IEC 60947-5-1</p>
Product certifications	<p>CSA</p> <p>TÜV</p> <p>UL</p>
IP degree of protection	<p>IP40(Enclosure) conforming to EN/IEC 60529</p> <p>IP20(Terminals) conforming to EN/IEC 60529</p>
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)

Ordering and shipping details

Category	22477 - SAFETY MODULES (PREVENTA)
Discount Schedule	I11
GTIN	00785901974000
Nbr. of units in pkg.	1
Package weight(Lbs)	0.84
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	DE

Contractual warranty

Period	18 months
--------	-----------