



RED & RED I

MULTI-PURPOSE RED GREASE



FEATURES

- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Remains effective at extremely high temperatures 450°F (232°C)
- Reduces friction and vibration
- Resists shock
- Red color allows easy visual inspection
- Penetrates quickly
- Non-melting
- NLGI Grade 2
- Exceptional adhesive and cohesive properties, resists throw-off at high speeds

APPLICATIONS

- Automotive
- Aviation
- Cables
- Cams and Pistons
- Chains
- Guide Rails
- Latches
- Marine
- Open Gears
- Overhead Door Tracks
- Packaging
- Slide Conveyors



PROPERTIES

Color:
Red

Penetration (ASTM D-217)
(Worked 60 Strokes):
250 – 265

NLGI Grade:
No. 2

Dropping Point:
550°F (288°C) non-melting

Shell Four Ball, EP (ASTM D-2596):
400 kg

Load Wear Index:
70

Timken OK Load (ASTM D-2509):
65 lbs.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

PACKAGE

Net Fill
11 oz. (312 grams) aerosol

Part No.
05816

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Website: www.lpslabs.com

©2012 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2149 • Rev. 5/2012