

INSTALLATION ACCESSORIES – SIZE 7

Unless indicated otherwise, accessories can be used with either poly or metal plugs and receptacles.

HANDLES

LARGE HANDLE w/NPT	Part #
2"	5T7P0N20
2 1/2"	5T7P0N25
3"	5T7P0N30

LARGE HANDLE w/CORD GRIP Cable Range	Part #
2.062 - 2.188"	5T7P0JT1
2.188 - 2.312"	5T7P0JT2
2.312 - 2.438"	5T7P0JT3
2.437 - 2.625"	5T7P0KT1
2.625 - 2.812"	5T7P0KT2

STRAIGHT HANDLE W/BUSHING w/Cable Range	Part #
2.09 - 2.25"	5T7P0D57
2.25 - 2.44"	5T7P0D62
2.44 - 2.67"	5T7P0D68
2.67 - 2.87"	5T7P0D73

ANGLES

METAL ANGLE	Part #	Notes
0°	596M0	
Extended 60°	5T7M6	
Extended 60° with 68 mm spacer.	5T7M6-68	Provides space for Cable Reducing Adapters.

BOXES

BOX ANGLE WITH METAL BOX w/NPT	Part #
0° 2"	7T7F0N20
0° 2 1/2"	7T7F0N25
0° 3"	7T7F0N30
0° 3 1/2"	7T7F0N35
0° 4"	7T7F0N40

MISCELLANEOUS ACCESSORIES

PROTECTIVE CAP	Part #	Notes
	35-2A126	For Male Devices Only.
CABLE REDUCING ADAPTERS		
	PT535FX350-3	Reducer for 500 MCM Fine Stranded or Flexible Wire.
	PT500R350-3	Reducer for 500 MCM Coarse Stranded or Building Wire.
	PT400R350-3	Reducer for 400 MCM Wire.
SPACER		
	5T7M0-68	68mm (2.68») spacer is used (included) with metal 60° angle.
	5T7M0-115	115mm can be used when mounting to a panel - though the metal straight adapter is preferred.
RECEPTACLE LOCKING PIN		
	LP-843	Requires Padlockable Pawl option (-843) on receptacle.

DR / PN

DIMENSIONS – Provided in inches

Dimensions are for reference only and may change depending on accessories used. For precise dimensions contact MELTRIC Engineering.

