

# Sockets, Drive Tools, Accessories



## 1/4" DRIVE DEEP LENGTH SOCKETS - 6 POINT

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.

## 1/4" DRIVE DEEP LENGTH SOCKETS - 6 POINT



Product ID No.	in.	B	C	D	E	L	Weight lbs.	ASME Spec.
J4706L	3/16"	5/16"	15/32"	9/32"	1-21/32"	2"	0.05 lbs.	ASME B107.1
J4707L	7/32"	11/32"	15/32"	3/8"	1-21/32"	2"	0.05 lbs.	ASME B107.1
J4708L	1/4"	25/64"	15/32"	3/8"	1-1/2"	2"	0.05 lbs.	ASME B107.1
J4709L	9/32"	7/16"	15/32"	3/8"	1-1/2"	2"	0.05 lbs.	ASME B107.1
J4710L	5/16"	15/32"	15/32"	3/8"	1-1/2"	2"	0.06 lbs.	ASME B107.1
J4711L	11/32"	1/2"	1/2"	5/8"	1-1/2"	2"	0.06 lbs.	ASME B107.1
J4712L	3/8"	9/16"	9/16"	5/8"	1-27/64"	2"	0.08 lbs.	ASME B107.1
J4714L	7/16"	37/64"	39/64"	5/8"	1-27/64"	2"	0.09 lbs.	ASME B107.1
J4716L	1/2"	11/16"	11/16"	5/8"	1-27/64"	2"	0.13 lbs.	ASME B107.1
J4718L	9/16"	3/4"	3/4"	5/8"	1-27/64"	2"	0.14 lbs.	ASME B107.1



## 1/4" DRIVE METRIC DEEP LENGTH SOCKETS - 6 POINT

**METRIC**



Product ID No.	mm	B	C	D	E	L	Weight lbs.	ASME Spec.
J4704LM	4	7.0	11.7	5.0	22.0	50.5	0.04 lbs.	ASME B107.5M
J4705LM	5	7.9	11.7	7.0	22.0	50.5	0.04 lbs.	ASME B107.5M
J47055LM	5.5	8.8	11.7	7.0	22.0	50.5	0.04 lbs.	ASME B107.5M
J4706LM	6	9.4	11.7	9.5	22.0	50.5	0.04 lbs.	ASME B107.5M
J4707LM	7	10.8	11.7	9.5	22.0	50.5	0.04 lbs.	ASME B107.5M
J4708LM	8	11.7	11.7	10.5	29.2	50.5	0.06 lbs.	ASME B107.5M
J4709LM	9	12.7	12.7	15.5	29.2	50.5	0.06 lbs.	ASME B107.5M
J4710LM	10	14.4	14.4	16.0	36.0	50.5	0.07 lbs.	ASME B107.5M
J4711LM	11	15.6	15.6	16.0	36.0	50.5	0.09 lbs.	ASME B107.5M
J4712LM	12	16.5	16.5	16.0	36.0	50.5	0.11 lbs.	ASME B107.5M
J4713LM	13	17.6	17.6	16.0	36.0	50.5	0.15 lbs.	ASME B107.5M
J4714LM	14	19.6	19.6	16.0	36.0	50.5	0.15 lbs.	ASME B107.5M
J4715LM	15	21.2	21.2	16.0	36.0	50.8	0.20 lbs.	ASME B107.5M

