

1/4" DRIVE METRIC STANDARD LENGTH SOCKETS - 6 POINT

METRIC

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.



Product ID No.	mm	B	C	D	E	L	Weight lbs.	ASME Spec.
J4704M	4	6.9	12.0	4.5	10.3	22.2	0.01 lbs.	ASME B107.5M
J47045M	4.5	7.9	12.0	4.5	10.3	22.2	0.01 lbs.	ASME B107.5M
J4705M	5	7.9	12.0	4.5	10.3	22.2	0.02 lbs.	ASME B107.5M
J47055M	5.5	8.5	12.0	4.5	10.3	22.2	0.02 lbs.	ASME B107.5M
J4706M	6	9.4	12.0	5.5	10.3	22.2	0.02 lbs.	ASME B107.5M
J4707M	7	10.8	12.0	6.5	12.0	22.2	0.02 lbs.	ASME B107.5M
J4708M	8	12.0	12.0	7.5	13.7	22.2	0.04 lbs.	ASME B107.5M
J4709M	9	13.0	13.0	9.0	13.7	22.2	0.03 lbs.	ASME B107.5M
J4710M	10	14.6	14.6	9.0	13.7	22.2	0.04 lbs.	ASME B107.5M
J4711M	11	15.8	15.8	9.0	13.7	22.2	0.05 lbs.	ASME B107.5M
J4712M	12	16.7	16.7	9.0	13.7	22.2	0.05 lbs.	ASME B107.5M
J4713M	13	17.5	17.5	9.0	13.7	22.2	0.05 lbs.	ASME B107.5M
J4714M	14	19.0	19.0	9.0	14.2	22.2	0.06 lbs.	ASME B107.5M
J4715M	15	20.3	20.3	9.0	14.2	22.2	0.08 lbs.	ASME B107.5M
J4716M	16	22.2	22.2	9.5	14.2	22.2	0.09 lbs.	ASME B107.5M

